

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐  
2. NAME OF OPERATOR  
SUNDANCE OIL COMPANY  
3. ADDRESS OF OPERATOR  
Suite 510, 1776 Lincoln St., Denver, CO 80203  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FSL, 1901' FWL, Unit N  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  
TEST WATER SHUT-OFF ☐ ☐  
FRACTURE TREAT ☐ ☐  
SHOOT OR ACIDIZE ☐ ☐  
REPAIR WELL ☐ ☐  
PULL OR ALTER CASING ☐ ☐  
MULTIPLE COMPLETE ☐ ☐  
CHANGE ZONES ☐ ☐  
ABANDON\* ☐ ☐  
(other) RAN PRODUCTION CASING

5. LEASE  
NM-15019  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Cone Federal  
9. WELL NO.  
10  
10. FIELD OR WILDCAT NAME  
Tomahawk, San Andres  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 30, T.7S., R.32E.  
12. COUNTY OR PARISH  
Roosevelt  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4403' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 7 7/8" hole to total depth of 4325'. Logged. Ran 110 jts. 4 1/2", 10.5# K-55 casing. Set at 4325'. Cemented w/300 sx 50/50 Pozmix mixed with 2% gel, 8# salt, 1/4# Celloflakes. Plug down at 1 p.m. 5/29/79. Pressured up to 1500# for 10 minutes, held okay. Rig released at 3 p.m. 5/29/79.

RECEIVED

JUN 4 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Richard O. Dimit TITLE VP, Production DATE May 31, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 4 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side