

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐2. NAME OF OPERATOR
SUNDANCE OIL COMPANY3. ADDRESS OF OPERATOR
Suite 510, 1776 Lincoln St., Denver, CO 802034. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL, 1901' FWL, Unit F
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) SET PRODUCTION CASING

RECEIVED

JUN 21 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole to total depth of 4305'. Ran logs. Ran 105 jts. of 4 1/2", 10.5#, K-55 casing to 4305'. Cemented with 300 sx 50/50 pozmix with 2% gel, 8# salt, 1/4# Celloflakes. Plug down at 1:15 a.m. 6/14/79. Pressured to 1500#, held okay. Released rig at 3 a.m. 6/14/79. PBD 4260'. WOCU.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Richard O. Dimit TITLE VP, Production DATE June 18, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:ACCEPTED FOR RECORD
JUN 21 1979
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO