

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYN. M. OIL CONS. COMMISSION
P. O. BOX 1980
HOMES, NEW MEXICO 88440Form Approved
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐2. NAME OF OPERATOR
Flag-Redfern Oil Company3. ADDRESS OF OPERATOR
P.O. Box 11050 Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 600' FWL

AT TOP PROD. INTERVAL: 660

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒

SUBSEQUENT REPORT OF:

(other)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Westall Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME
Tomahawk (San Andres)11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 29, T-7-S, R-32-E12. COUNTY OR PARISH
Roosevelt13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4482 KDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugging Reason: Operating cost exceeds revenue from oil production and well is no longer economical to produce.

1. Spot a 25 sx class "C" cement plug from PBTD (4283') to 3914'.
 2. Pull uphole 400'. Load hole with mud laden fluid (25 sx gel / 100 bbls wtr)
 3. Determine freepoint of 4½" casing. Shoot casing off just above freepoint, Pull and lay down casing.
 4. Spot a 25 sx class "C" cement plug at casing stub (50' inside stub and 50' outside).
 5. Spot a 35 sx class "C" cement plug from 1832' to 1700'. (8 5/8" casing shoe)
- Continued on next sheet-

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kelly J. Gorman TITLE Engineer DATE 7-27-84

APPROVED (This space for Federal or State office use)

(Orig. Sgd.) PETER W. CHESTER

APPROVED BY _____

TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

AUG 9 1984

*See Instructions on Reverse Side