The State of the S P. O. BOA

HOBBS, NEW LIEMICU 88240

Form 3160-5 (December 1989)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: September 30, 1990

5 Lease Designation and Serial No

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS)
0011011						

m for proposals to drill or to deepen or reentry to a different reservoir.

LC-060978 6 If Indian. Allottee or Tribe Name

Do not use this form for proposals to drill of to desper. Use "APPLICATION FOR PERMIT—" for such proposals	7 If Unit or CA, Agreement Designation
SUBMIT IN TRIPLICATE	MILNESAND (SA) UNIT
1. Type of Well Name of Operator	8. Well Name and No 516 9 API Well No - OC (4/-/C 2 y) 10 Field and Pool, or Exploratory Area MILNESAND (SAN ANDRES 11. County or Parish, State ROOSEVELT
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF I	NOTICE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION X Notice of Intent	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Note Report results of multiple completion on Well Completion or Recognizing Report and Log form

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work

Cast iron bridge plug is set or will be set. Well will be pressure tested for mechanical integrity to 500psi for 30 minutes. BLM will be notified in advance in order to witness test, if desired.

)		
4. I hereby certify that the foregoing is true and correct	Tie OPERATIONS MANAGER	Date 10-29-92
(This space for Federal or State office usey		APPENDE
Approved by	7.00	PETER W. Pale PSTER
Conditions of approval it any See allacket	<i>i</i>	NOV 1 7 1992
Title 18 U.S.C. Section 1000 makes in a crime for inviners in knowing representations as to any marter is thin its unisductive.	310	The United States and take Statious or fraudulent statement REAL GREAAD VANAGEMENT
	*See Instruction on Reverse Side	ROSWELL RESOLACE AREA

Additional Stipulations for Casing Integrity Test

- 1. The cast iron bridge plug shall be set within 100 ft. of the upper most perforations or casing shoe if completed open hole.
- 2. Also notify the New Mexico Oil Conservation Division (NMOCD) prior to test.