6. IF INDIAN, ALLOTTEE OR TRIBE NAM  ack to a different reservoir.  oposals.)  7. Unit agreement name  8. FARM OR LEASE NAME
State requirements 3 1980  State requirements 3 1980  10. FIELD AND POOL, OR WILDCAT  Wildcat  Wildcat  R-37EHOBBS, NEW MEXICO  Sec. 27 T-7S R-37E  12. COUNTY OR PARISH 13. STATE  ROOSEVELT NM
SUBSEQUENT REPORT OF:  WATER SHUT-CFF FRACTURE TREATMENT SHOOTING OR ACIDIZING Other) plug; back & set prod. casing (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
R

nent to this work.) \*

Drill 7 7/8" hole to 9202'. Set 150' plug @ 8320'-8170 . Cement with 50 sacks Class "H"

150' plug @ 7045-6895' Cement with 50 sacks Class "H".

100' plug @ 6295-6195' Cement with 45 sacks Class "H"

100' plug @ 4750-4650' Cement with 35 sacks Class "H"-: % calcium

Run 4 1/2" 10.5# K-55 Stc casing & set at 4626'. Cemen: with 450 sacks 50/50 poz W/6# salt per sack, 2% gel & 4% CFR-2. Plug down 2:15 a.m. 9-15-80

/ 7		
18. I hereby certify that the foregoing is true and correct		
	TITLE Superintendent	DATE10-25-80
(This space for Federal of Scientific FOR RECORD PETER W. CHESTER CONDITIONS OF APPROVAL, IF ANY:	ritle:	DATE
NOV 4 1980		

U.S. GEOLOGICAL SURVESce Instructions on Reverse Side ROSWELL, NEW MEXICO