. OF COPIES RECEIVED			Form C-103 Supersedes Old
DISCRIBUTION			C-102 and C-103
SZ ITA FE	NEW MEXICO OIL CONSE	RVATION COMMISSION	Effective 1-1-65
FILE			
			5a. Indicate Type of Lease
U.S.G.S.			State XX Fee
LAND OFFICE			5, State Oil & Gas Lease No.
OPERATOR			LG-3029
SUN	DRY NOTICES AND REPORTS ON PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BA	CK TO A DIFFERENT RESERVOIR.	
(DO NOT USE THIS FORM TON USE **APPLI	CATION FOR PERMIT -** (FORM C-101) FOR SUCH	PROPOSALS.)	7. Unit Agreement Name
OIL GAS WELL	OTHER-		8. Farm or Lease Name
2. Name of Operator			State
SUNDANCE OIL COMPANY			9. Well No.
3. Address of Operator			
Suite 910, 1776 Lincoln St., Denver, CO 80203			2
4 Location of Well			10. Field and Pool, or Wildcat
n –	660 FEET FROM THE North	LINE AND 660 FEET FROM	Tomahawk, San Andres
THE West LINE, SECTION 32 TOWNSHIP 7S RANGE 32E NME			ΔΗΗΗΗΗΗΗΗ
THE West Line, SE	CTION TOWNSHIP	RANGE NMPM.	
	15. Elevation (Show whether	DF, RT, GR, etc.)	12, County
		-	Roosevelt
	4442.7'GL		
<sup>16.</sup> Chee	ck Appropriate Box To Indicate N	ature of Notice, Report or Ut	her Data
	INTENTION TO:	SUBSEQUENT	REPORT OF:
			المعار
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
[]		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
TEMPORARILY ABANDON	CHANGE PLANS	CASING TEST AND CEMENT JOB	
PULL OR ALTER CASING		OTHER	
	· []		
OTHER			
	11	ails, and give pertinent dates, including	estimated date of starting any proposed
	d Operations (Clearly state all pertinent det		
work) SEE RULE 1103.	ed Operations (Clearly state all pertinent det	-	
Well was spudded at	ed Operations (Clearly state all pertinent det : 1:45 p.m. on 1/6/81. Dri # surface casing. Set at 1 Class C, 2% CaCl <sub>2</sub> . Circula	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx (	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786' Cemented with 250	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx ( okay. WOC.	: 1:45 p.m. on 1/6/81. Dri # surface casing. Set at 1 Class C, 2% CaCl <sub>2</sub> . Circula	lled 12 1/4" surface hol 786'. Cemented with 250 ted 10 sx cement. Press	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx ( okay. WOC.	: 1:45 p.m. on 1/6/81. Dri	lled 12 1/4" surface hol 786'. Cemented with 250 ted 10 sx cement. Press	e to 1799'. Ran 48 ) sx Class C, 3%
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx ( okay. WOC.	1:45 p.m. on 1/6/81. Dri surface casing. Set at 1 Class C, 2% CaCl <sub>2</sub> . Circula	<pre>11ed 12 1/4" surface hol 786'. Cemented with 250 ted 10 sx cement. Press of my knowledge and belief.</pre>	e to 1799'. Ran 48 ) sx Class C, 3% sured up to 1000#,
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx ( okay. WOC.	1:45 p.m. on 1/6/81. Dri surface casing. Set at 1 Class C, 2% CaCl <sub>2</sub> . Circula	<pre>11ed 12 1/4" surface hol 786'. Cemented with 250 ted 10 sx cement. Press of my knowledge and belief.</pre>	e to 1799'. Ran 48 ) sx Class C, 3% sured up to 1000#,
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx ( okay. WOC.	nation above is true and complete to the beat	lled 12 1/4" surface hol 786'. Cemented with 250 ted 10 sx cement. Press	e to 1799'. Ran 48 ) sx Class C, 3% sured up to 1000#,
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx ( okay. WOC. 18. 1 hereby certify that the inform SIGNED Richard (). Dim	nation above is true and complete to the best	<pre>11ed 12 1/4" surface hol 786'. Cemented with 250 ted 10 sx cement. Press of my knowledge and belief.</pre>	e to 1799'. Ran 48 ) sx Class C, 3% sured up to 1000#,
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx ( okay. WOC. 18. 1 hereby certify that the inform SIGNED Richard (). Dim	nation above is true and complete to the best	<pre>11ed 12 1/4" surface hol 786'. Cemented with 250 ted 10 sx cement. Press of my knowledge and belief.</pre>	e to 1799'. Ran 48 ) sx Class C, 3% sured up to 1000#,
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx ( okay. WOC.	ation above is true and complete to the best final true and comple	<pre>11ed 12 1/4" surface hol 786'. Cemented with 250 ted 10 sx cement. Press of my knowledge and belief.</pre>	e to 1799'. Ran 48 ) sx Class C, 3% sured up to 1000#,
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx ( okay. WOC.	nation above is true and complete to the best Minute Signal by Southors TITLE	<pre>11ed 12 1/4" surface hol 786'. Cemented with 250 ted 10 sx cement. Press of my knowledge and belief.</pre>	e to 1799'. Ran 48 ) sx Class C, 3% sured up to 1000#, on DATE <u>1/13/81</u>
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx ( okay. WOC. 18. I hereby certify that the inform SIGNED Richard Chimm Or: Jecz	nation above is true and complete to the best Minute Signal by Southors TITLE	<pre>11ed 12 1/4" surface hol 786'. Cemented with 250 ted 10 sx cement. Press of my knowledge and belief.</pre>	e to 1799'. Ran 48 ) sx Class C, 3% sured up to 1000#,
Well was spudded at jts. of 8 5/8", 24 Econolite, 200 sx ( okay. WOC.	nation above is true and complete to the best Minute Signal by Southors TITLE	<pre>11ed 12 1/4" surface hol 786'. Cemented with 250 ted 10 sx cement. Press of my knowledge and belief.</pre>	e to 1799'. Ran 48 ) sx Class C, 3% sured up to 1000#,