Form 9-331 Dec. 1973 DBS, NEW MEXICO 88244	Form Approved. Biodget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM 18846
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a diff reservoir, Use Form 9–331–C for such proposals.)	-
	8. FARM OR LEASE NAME U.S.
well well other	9. WELL NO.
2. NAME OF OPERATOR	4
EL RAN, INC.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Chaveroo (SA)
P. O. BOX 911, LUBBOCK, TEXAS 79408	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space	
below.) AT SURFACE: Unit Letter L 1650FSL & 990 F	Sec. 34, T7S, R32E
AT TOP PROD. INTERVAL: Same	The second second reader and second
AT TOTAL DEPTH: 4262' KB	Roosevelt New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOT	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT	4501 4 GR
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9–330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

El Ran, Inc. proposes to plug and abandon the above referenced well because it has become uneconomical to operate. Well was produced from the San Andres Formation from perforations at 4209' to 4288'. Spot CIBP @ 4159'? We intend to cut the 4½" casing off at 3300' KB. Load hole with 9½# Mud Laden Fluid. Spot 100' plug at 3300'. Spot 100' plug across the Yates Formation @ **2476**'. Pull up to bottom of surface pipe at 1712'KB and spot 100' plug and a 50' plug at surface with appropriate marker. Well site will be conditioned within thirty days thereafter for final approval of abandonment. We anticipate plugging to begin approximately the second week in August. We will notify you 24 hours in advance of

- 0	
* Cap CIBP W/35 cmt,	
* Cap CIBP W/35 cmt, ** tag plug. ** tag plug. ** tag plug. ** tag plug.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED TITLE Vice-Pres	sident
(This space for Federal or Si	tate office use)
APPROLEDIE (BEL) PETER W. CHESTER	
CONDITIONS OF APPROVAL, IE ANY:	
*See Instructions on Re	verse Side
Service - Frank Stranger	



۰.
