Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLIC
(Other Instructions :
verse side)

Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 18846

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

SEP ... 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

1.

| OIL WELL | X | GAS WELL | ☐ | OTHER |

2. NAME OF OPERATOR

El Ran, Inc.

3. ADDRESS OF OPERATOR

1603 Broadway, Lubbock, Texas 79401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650' FSL & 990' FWL

14. PERMIT NO.

Verbal

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4501.4 Gr.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

U. S.

9. WELL NO.

#4

10. FIELD AND POOL OR WILDCAT

Chaveroo (SA)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 34, T7S, R32E

12. COUNTY OR PARISH | 13. STATE

Roosevelt | New Mexico

16.
Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANS	(Other) Running Casing	
(Other)			

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

9/16/80 Surface casing set 1712' and cemented with 575 sacks
common cement with 10# salt and 1/4# Flocele. Circulated
49 sacks to surface. Blowout preventor was installed and
pressured to 1000# for 30 minutes.

9/23/80 Set 4 1/2" 10.5# casing to 4362' and cemented with 175
sacks 50-50 POZ Class "C".

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE _____ Agent _____ DATE _____ 9/23/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL

ACCEPTED FOR RECORD
V. Chester
SEP 29 1980
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side