		Oil Cons.			
Form 3160-5	UNIT	ED ATES N.M. DIV-Dist 2	FORM APPROVED		
(JUNE 1990)			Budget Bureau No. 1004-0135		
v - · ·	BUREAU OF	LAND MANAGEMENT NIM 88210	Expires: March 31, 1993		
		Allesia, IVIM 00210	5. Lease Designation and Serial No.		
	SUNDRY NOTICES	NM-84732			
Do not u	se this form for proposals to c	5. If Indian, Allottee or Tribe Name			
	Use "APPLICATION				
	SUBMI	T IN TRIPLICATE	7. If Unit or CA, Agreement Designation		
1. Type of Wel]	19-1			
Oil	Gas	s			
X Well Well Other 2. Name of Operator STRATA PRODUCTION COMPANY			S-Well Name and No.		
2. Name of Op		Sunrise Federal #1			
	STRATA PR	9. API Well No.			
3. Address and	Telephone No. P. O. Box 1	30-041-20577			
	Roswell, Nev	10. Field and Pool, or Exploratory Area			
4. Location of	Well (Footage, Sec., T., R., M., or Sur	Chaveroo San Andres			
	1980' FNL 8	11. County or Parish, State			
	Section 21-7	Roosevelt County, New Mexico			
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA					
T	YPE OF SUBMISSION	TYPE OF ACTION			
X	Notice of Intent	Abandonment	Change of Plans		
		Recompletion	New Construction		
	Subsequent Report	X Plugging Back	Non-Routine Fracturing		
		Casing Repair	Water Shut-Off		
	Final Abandonment Notice	Altering Casing	Conversion to Injection		
		OTHER	Dispose Water		
			Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		
12 Describe D	anaged on Completed Operations (Cla	active state all pertinent details, and give pertinent dates, including estim			

B. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Existing perfs 4365' - 4494', 19 shots.

Set CIBP @ 4325'. Cap w/35' cement. Circ hole w/9# per gallon mud. Spot 150' plug, 25 sx of cement, from 3670' - 3570' across top of San Adres @ 3620'. Cut csg +/- 3300'. TOC 3345' from csg bond log. Spot 100' plug half in half out of cut off 3250' - 3350', 35 sx cement. Spot plug across 8 5/8" csg shoe @ 2100'. 75 sx of cement 2200' - 2000'. Spot 100' plug from 1000' - 900', 35 sx cement. Spot surface plug to surface to 60', 25 sx cement. Cut off wellhead. Install dry hole marker, and remove equipment. Rip and reseed per BLM specifications.



I hereby certify that the foregoing is true and correlation	rect	
Signed Ally MButt	Title Production Records	Date 12/30/02
(This space for Federal or State office use)		
Approved by	Title COD	3 MONTH PERIOD
Conditions of approval, if any:	PPROVED FOR	
		NIL 2,2003
Title 18 U.S.C. Section 1001, makes it a crime for any perepresentations as to any matter within its jurisdiction.	erson knowingly and willfully to make a structure of t	ne United States any false, fictitious or fraudulant statements or
GWW	* See Instruction on Reverse Side	F3160-5.WK1

RECEVED

5005 DEC 31 VW 8: 33

BORENCICI CENCE

the state