

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2038
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name I
2. Name of Operator Apache Corporation	8. Farm or Lease Name Paul
3. Address of Operator 7666 East 61st Street, 500 Triad Center, Tulsa, OK 74133-1201	9. Well No. 1
4. Location of Well UNIT LETTER I, 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 17, TOWNSHIP 8S, RANGE 34E, NMPM.	10. Field and Pool, or Wildcat West Milnesand SA
15. Elevation (Show whether DF, RT, GR, etc.) 4297 Ground	12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. (See attached wellbore diagram for details) Operations to begin 11/87.

1. Notify Oil Conservation Division 24 hours prior to beginning operations (505) 393-6161.
2. POH w/rods and pump.
3. POH w/tbg anchor and tbg.
4. Spot 25 sx Class "C" cmt plug f/4500'4720'.
5. Displace hole w/plug mud consisting of 10#/gal brine and 25# gel/bbl.
6. Free point & cut off 5 1/2" csg. POH w/csg. (Approx 3400').
7. Spot 35 sx Class "C" cmt plug at 5 1/2" csg cut off, w/at least 50' cmt above & below cut off
8. Spot 35 sx Class "C" cmt plug, 1720-1840 (Across shoe of 8-5/8" inter csg).
9. Spot 40 sx Class "C" cmt plug 3-110' (covers surface plug and shoe of 13-7/8" surface csg)
10. Cut off 8-5/8" & 13-3/8" csg 3' below ground level. Weld on cap and 4" diameter pipe. Pipe will have well name, number and location permanently engraved and will extend at least 4' above ground level.
11. Restore location.

Tan - stop plug & ss done by

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie W. Seay

TITLE Production Engineer

DATE 9/30/87

Eddie W. Seay

APPROVED BY Oil & Gas Inspector
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE OCT 6 1987