## WELL DATA

## For Water Disposal Well

Α.

- (1) Pauley Petroleum, Inc. #1 State. Located 660' FNL and 1980' FEL, Section 16, T-7-S, R-33-E, Roosevelt Co., N.M.
- (2) <u>Casing Record</u> 398' 12<sup>3</sup>/<sub>4</sub>" casing set @ 398' - 400 sx C1 "C" w/ 2% CaC1. Cement Circulated 3922' 8<sup>5</sup>/<sub>8</sub>" casing set @ 3922' - 1500 sx Howco Lt & C1 "C" Cement Circulated 8470' 4<sup>1</sup>/<sub>2</sub>" casing set @ 8470' - 475 sx Posmix Top Cement-7100' (Top Cement determined by Temperature Survey) Well plugged back in accordance w/ Form C-103 filed 6/16/82, and Form C-105 filed 7/12/82.
- (3)  $3850\pm 2\frac{3}{8}$  " Eue 8 RD J-55 Tubing (unlined)
- (4) Baker Model "D" Packer w/ Baker Hold down to be set @ 3855'

## Β.

- (1) San Andres Formation No field or pool.
- (2) 3862-74' Perforated
- (3) Well originally drilled to test Bough "C" for oil dry.
- (4) Original Perforations: 8376-86', Cemented w/ 70 sx cmt. on top of Baker Model "R" Packer @ 8208'.
- (5) No other producing zones higher or lower near well.

.

RECEIVED

JUL 1 4 1982 Hobbs Office

-.