Elen Matol	N. M. OIL CONS.	COMMISSION			
21. (y. 1663)	L. TEDPS ABOX 1980	STEMIT IN THE JCATE		ed. 511 No. 42-3:1424.	
UE	PARTMENT OF HOBBS, NEW ME GEOLOGICAL SURVEY	AICO 88240	5. LEASE DESIGNATION	AND SFRIAL NO.	
	NM-14808				
(Do not use this form	NOTICES AND REPORTS (for proposals to drill or to deepen or plug "APPLICATION FOR PERMIT—" for such p	back to a different reservoir	6. IF INDIAN, ALLOTTE	E OR TEIBE NAME	
I. OIL GAS WELL WELL	7. UNIT AGREEMENT NAME				
NAME OF OPERATOR	8. FARM OR LEASE NAME				
NRM Petroleum Co	Bilbrey Federal				
. ADDEESS OF OPERATOR	9. WELL NO.				
900 Bldg of the	1				
LOCATION OF WELL (Report See also space 17 below.) At surface	10. FIELD AND POOL, OB WILDCAT				
600' FSL & 1980	Wildcat				
000 151 & 1980	11. SEC., T., R., M., OR BLK. AND SUBVEY OR ABEA				
			Sec 29, T7S, 1	R38E	
4. PERMIT NO.	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)			12. COUNTY OF PARISH 13. STATE	
NM 14808	4004.7 GR		Roosevelt	NM	
^{6.} Cl	neck Appropriate Box To Indicate N	lature of Notice, Report, or (Other Data		
NOTICE	SUBSEQ	EQUENT REPORT OF :			
TEST WATER SHUT-OFF	PULL OB ALTER CASING	WATER SHUT-OFF	BEPAIRING W		
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA		
SHOOT OF ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMEN		
REPAIR WELL	CHANGE PLANS	(Other)			
(Other)		(Norg: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			
DESCRIBE PROPOSED OR COMPL proposed work. If well nent to this work.) *	LETED OPERATIONS (Clearly state all pertinen is directionally drilled, give subsurface locat	t details and give portinent detag	including optimated date		
The Bilbrey Federa	1 #1 was spudded $8-1-82$, s	Set 40' conductor. I	Drilled to 401'.	ran	

400' 8 5/8" 23# csg & cmt w/300 sx class "C" cmt & circ. Drilled to 4651'. Core #1 @ 4651'-4711'- rec 60' no show, Core #2 @ 4711'-4741'- rec 30' no show. Drilled from 4741' to 4770'. Core #3 @ 4770'-4830'- rec 60' no show. Ran open hole logs. Ran DST #1 @ 4738'-4830'- rec 62' very slighty GCM. Spot plug #1 60 sx @ 3900'-3800', #2 60 sx @ 2712'-2612', #3 60 sx @ 450'-350', #4 15 sx @ surface. Released rig 8-14-82.



.8. I hereby certify t	that the gregoing is	true and correct		
SIGNED In			TITLE Operations Manager	DATE
(This space for l	Federal or State office			
	Sgd.) PETER W FAPPROVAL IF AN IUV 1	TY :	TITLE	DATE
	یم در ا د بر	*S	ee Instructions on Reverse Side	
	*. *.			