

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well
2. NAME OF OPERATOR
Bliss Petroleum Inc.
3. ADDRESS OF OPERATOR
P. O. Box 1817, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)
AT SURFACE: 660' FNL & 660' FWL of Sec. 31
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Production Casing

SUBSEQUENT REPORT OF



- 59 LEASE NM 15332
6. IF INDIAN, A. LOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Federal PB
9. WELL NO.
10. FIELD OR WILDCAT NAME
Undesignated
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
31-T8S-R38E
12. COUNTY OR PARISH 13. STATE
Roosevelt NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3995' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to TD 9525'

Ran:

- | | |
|---|----------|
| 1 - HOWCO Guide Shoe | 1.00' |
| 1 jts. - 5 1/2", 17#, N-80, LT&C Csg. | 40.12' |
| 1 - HOWCO Float Shoe | 2.50' |
| 56 jts. - 5 1/2", 17#, N-80, LT&C Csg. | 2387.55' |
| 161 jts. - 5 1/2", 17#, K-55, LT&C Csg. | 6915.10' |
| 5 jts. - 5 1/2", 17#, N-80, LT&C Csg. | 208.81' |
| Total | 9555.08' |

Set @ 9522.11' KB

Cemented w/375 sx. 50-50 POZ. "C" plus 0.6% CF9 plus 0.3% TF4 & 3% KCL. Bumped plug on 3-5-82. Float Held OK.

Pressure tested casing to 1500 psi for 30 min. Held OK.

Subsurface Safety Valve Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Paul Bliss TITLE President DATE 4-8-82

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY: 63

TITLE _____ DATE _____

APR 27 1982
U.S. GEOLOGICAL SURVEY
POSWELL, NEW MEXICO

*See Instructions on Reverse Side