

UNITED STATES HOBBBS, NEW MEXICO
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Bliss Petroleum, Inc.
3. ADDRESS OF OPERATOR
P. O. Box 1817 Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660' FNL & 660' FWL of Section 31
AT SURFACE:
AT TCP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Set Surface Casing

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

X

RECEIVED
JAN 19 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

88240 CASE

NM 15332

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

~~FF~~ Federal PB

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR

AREA
Section 31, T8S, R38E

12. COUNTY OR PARISH 13. STATE

Roosevelt

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

KB-3995'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded w/ 17 1/2" bit at 4:30 P.M. on 1-13-82

Drilled to 420'.

Ran 1-13 3/8" Halliburton Guide Shoe - 1.00'

11 jts. - 13 3/8", 48# LT&C New Casing - 418.13'

Set at 419.13' KB

Cemented w/ 475 sx. Class "C" cement w/ 1% CaCl₂ & 1/4 #/sx. Cello-Seal.

Had good returns. Circulated to surface w/ 100⁺ sx. cmt.

Plug down at 4:25 A.M. on 1-16-82.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Paul Bliss TITLE President DATE 1-18-82

ACCEPTED FOR RECORD
ROGER A. CHAPMAN
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

JAN 20 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side