

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-actively log run on the well and a summary of all special tests conducted, including fluid stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy 1939' (+2390)	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt 1970' (+2359)	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
R. Salt 2250' (+2079)	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2250' (+2079)	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2356' (+1973)	T. Devonian	T. Menefee	T. Madison
T. Owen 2917' (+1412)	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3138' (+1191)	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3375' (+954)	T. Simpson	T. Gallup	T. Ignacio Quize
T. Clarieta	T. McKee	Base Greenhorn	T. Granite
T. Redbed	T. Ellenburger	T. Dakota	T.
T. Glinbury	T. Gr. Wash.	T. Morrison	T.
T. Tubb	T. Granite	T. Todilte	T.
T. Drift	T. Delaware Sand	T. Entrada	T.
T. Alb.	T. Bone Springs	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn.	T.	T. Pennian	T.
T. Cisco (Bough C)	T.	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 4050' to 4107'	No. 4, from to
No. 2, from 4150' to 4219'	No. 5, from to
No. 3, from 4248' to 4271'	No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet	
No. 2, from to feet	
No. 3, from to feet	
No. 4, from to feet	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0'	50'	50'	Surface				
50'	465'	415'	Redbed				
465'	552'	87'	Anhy				
552'	1140'	588'	Anhy & redbed				
1140'	1478'	338'	Salt				
1478'	1944'	466'	anhy & redbed				
1944'	2250'	306'	Salt				
2250'	2357'	107'	shale				
2357'	3010'	653'	salt & anhy				
3010'	3375'	365'	shale & anhy				
3375'	3449'	74'	lime				
3449'	3508'	59'	salt				
3508'	4344'	836'	lime & anhy				

RECEIVED

FEB 8 1983

O.C.D.
HOBBS OFFICE