

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ Dry Hole
2. NAME OF OPERATOR  
Le May Energy Corp. - Petroleum Bldg.
3. ADDRESS OF OPERATOR  
207 Shelby - Suite 200; Santa Fe, N.M. 87501
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2310' FSL & 330' FEL of Sec. 10  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

5. LEASE  
NM 18643
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Celsius Federal
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Undesignated
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 10, T8S, R36E
12. COUNTY OR PARISH  
Roosevelt
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4101 KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU DA&S Plugging Equip.  
Ran 4 1/2" CIBP & set @ 4651' KB.  
Ran dump bailer & spotted 38' cmt. on top of BP. PBD @ 4611'.  
Ran 2 3/8" tbg. inside 4 1/2" & circ. hole w/MLF.  
Cut 4 1/2" off @ 4005' KB. Pulled & laid dwn. 96 jts. csg..  
Ran 2 3/8" tbg. & spotted cement plugs:  
35 sk. cmt. plug from 3955'-4055'.  
50 sk. cmt. plug from 2255'-2355'.  
15 sk. cmt. plug from surface - 50'.  
Remove csg. hd.. Cut off 8 5/8". Installed dry hole marker.  
Work finished on 12-2-82'.

Subsurface Safety Valve: Manu. and Type

Set @ ..... Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Paul White TITLE Agent

DATE 12-6-82

APPROVED

(This space for Federal or State office use)

APPROVED BY W. J. CHESTER TITLE

CONDITIONS OF APPROVAL, IF ANY:

FEB 14 1983

\*See Instructions on Reverse Side