

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LEASE LC-065510


SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Pace Exploration, Inc.
3. ADDRESS OF OPERATOR
P.O. Box 588 Artesia, N.M. 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL & 1980' FFL, T17S, R35E
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. IF INDIAN, ALIOTHE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Yates Federal
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Wildcat
11. SEC., T., R., M., OR B.K. AND SURVEY OR AREA
Sec. 17-T7S-R35E
12. COUNTY OR PARISH
Roosevelt
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
KB 4253.2 GL 4240.2

- REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
- | | | |
|----------------------|-------------------------------------|--------------------------|
| TEST WATER SHUT-OFF | ☐ | ☐ |
| FRACTURE TREAT | ☐ | ☐ |
| SHOOT OR ACIDIZE | ☒ | ☐ |
| REPAIR WELL | ☐ | ☐ |
| PULL OR ALTER CASING | ☐ | ☐ |
| MULTIPLE COMPLETE | ☐ | ☐ |
| CHANGE ZONES | ☐ | ☐ |
| ABANDON* | ☐ | ☐ |
| (other) | | |



OIL & GAS
U.S. GEOLOGICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
- 11-12-82 Spud.
- 11-13-82 Set 8 5/8" 28# csg. @ 450', cemented w/200 sxs Class C Neat, tail in 80 sxs Class C 2% CaCl, cir. 60 sxs to pits.
- 11-19-82 Set 4 1/2" 9.5# J-55 Csg, set @ 4326' KB, 4313' GL, cnt. w/ 300 sxs 50/50 Poz C w/2% Gel, 5# salt, .3% Halad-4. Bump plug. Cement @ 3400' GL by temp. survey.
- 12-01-82 Propose to perf. @ 4273', 4277', 4282', 4290', & 4298', 2 shots/ft.
- 12-02-82 Propose to acidize w/1000 gallons MCA & ball out.

Subsurface Safety Valve: Manu. and Type None-Surface control Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *David R. Glass* TITLE President DATE 11-29-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS
CONDITIONS OF APPROVAL OF ANY: DATE

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

DEC 14 1982

602.
HOBBS OFFICE