

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SONDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Wallace Oil & Gas, Inc.	8. Form or Lease Name Tucker
3. Address of Operator 50 Penn Place, Suite 850, Okla. City, OK 73118	9. Well No. 1
4. Location of well UNIT LETTER <u>K</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>5</u> TOWNSHIP <u>7S</u> RANGE <u>33E</u> N.M.P.M.	10. Field and Pool, or wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) Gr. 4409', KB 4430	12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-9-84 Commenced drilling operations.

1-10-84 Drilled to 2412'. Ran 8 5/8", 24#, J55 ST&C casing, set at 2412'. Cemented with 850 sxs Pace setter lite, 1/4# cello seal. Ran 250 sxs Class C neat, followed up with 200 sxs Class C neat. Displaced with 152 bbls of water. Circulated 251 sxs cement to surface. Cement top to bottom. Bumped plug at 1200#, held for 30 min., held OK.

WOC 18 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie Seay TITLE Production Sec. DATE Jan. 11, 1984

APPROVED BY ORIGINAL SIGNED BY EDDIE SEAY TITLE OIL & GAS INSPECTOR DATE JAN 16 1984

CONDITIONS OF APPROVAL, IF ANY: