

H. M. GILBERT
P. O. BOX 19
HOBBS, NEW MEXICO 88240

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

RECEIVED

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-36486

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gallina Federal

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Tomahawk San Andres

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

31-7S-32E

12. COUNTY OR PARISH

Roosevelt

13. STATE
NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

BUR. OF LAND MGMT
ROSWELL DISTRICT

2. NAME OF OPERATOR

MorOilCo., Inc.

3. ADDRESS OF OPERATOR

P.O. Drawer I, Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660 FSL

620 FWL

Unit M

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4402.2 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

REPAIRING WELL

☐
☐
☐
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Spud & Set Surface

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/24/83 Spud well @9:00 a.m., drilled to 1306'.

11/24/83 Drilled to 1741'. Ran 43 joints 8-5/8" casing, 24#, set @1741'.
Cemented with 375 sx. Pace Setter Lite, 1/4# Celoseal, 2% CaCl,
200# Class C Cement with 2% CaCl. Circulated 15 sx. Plug down
@11:30 a.m. Shut-down 18 hr. WOC. Tested to 1000# for 30 minutes.
No decrease in pressure.

18. I hereby certify that the foregoing is true and correct

SIGNED

Frank J. Moya

TITLE Operator

DATE 11/28/83

(This space for Federal or State office use)

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY

DEC 12 1983

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ROSWELL, NEW MEXICO

*See Instructions on Reverse Side