

Form 9-331
Dec 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
MWJ PRODUCING COMPANY
3. ADDRESS OF OPERATOR
1804 FNB Bldg Midland, Texas 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY See space 17 below.)
AT SURFACE: 1980' FNL & 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

5. LEASE

NM-19626

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brown 21 Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Todd Wolfcamp (ext)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 21, T-7S, R-35E

12. COUNTY OR PARISH 13. STATE

Roosevelt

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

4226' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED

JAN 23 1984

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/13/84: MI & RU CU. Cut & dressed 5½" csg. Installed W/H & ran std SN & 240 jts 2-3/8" Buttress Thread tbg & w/2' of 241st jt, tagged btm. Flanged up w/240 jts tbg. SN @ 7745'. SD ON and for weekend.

1/16/84: RU Western Co & tstd csg to 3600 psi. Rel'd press & circ'd well w/2% KCL wtr. Sptd 1000 gals 15% HCL ac. POOH. LD 5 jts. Installed BOP. RU CRC & pulled Gamma Ray & Collar Locator from PBTD of 7753' to 7200'. Perf'd Wolfcamp from 7639-41', 7653-58', 7660-62', 7766-70' & 7674-86' 2 SPF w/.4" OD csg gun. RD CRC & ran Baker R-3 pkr, Std SN & 235 jts 2-3/8" B/T tbg. Removed BOP. Rev'd ac back in tbg. Set pkr @ 7574.57' w/14000# & flanged up. Press csg to 500 psi, OK. Acd @ 1/2 BPM @ 1500 psi. Inc'd to 1½ BPM @ 2500 psi at end. ISIP 2200 psi, 10 min 600 psi. Bled tbg off & CWI ON.

1/17/84: SITP vacuum. Chk'd FL @ 2000'. Swbd to pit 8 hrs, rec'd est 75 BF w/trace of oil. FL 7500'. CWI ON.

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Peter W. Chester

TITLE

Agent

DATE

1/18/84

ACCEPTED FOR RECORD

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

APPROVED BY
COMMISSIONER OF

PETER W. CHESTER

TITLE

DATE

JAN 17 1984

RECEIVED BY
FEB 20 1984
O. C. D.
ARTERY CHIEF

RECEIVED
FEB 27 1984
O. C. D.
HQBMS OFFICE