## INSTRUCTIONS

This form is to be filed with the  $a_1p_1p_1r_1$ . District Office of the Commission not later than  $a_1$  systifter the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and redo-activity loss run  $a_2$ , the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be meanined depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate exception state land, where six copies are required. See Bule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

D 1	Southeastern New Mexico				Northwestern New Mexico						
Rustler T. Anhy	1852	T Canyon		т	Ojo Alamo	T.	Penn, "B"				
							Penn. "C"				
							Penn. ('D')				
T. Yates	2192	T. Miss		T.	Cliff House	т.	Leadville				
		T. Devonia	n	T.	Menefee	T.	Madison				
		<b>a</b>		~	Defect Leaders	T	1711				
T. Grayburg		T. Montoya		Т.	Mancos	T.	McCracken				
T. San Andres		. T. Simpson		T.	Gallup	T.	Ignacio Qtzte				
T. Glorieta	4620	T. McKee		Ba	se Greenhorn	T.	Granite				
T. Paddock		T. Ellenbu		Т.	Dakota	т.					
T. Blinebry		T. Gr. Wash	1	T.	Morrison	T.					
T. Tubb	6094	T. Granite		T.	Todilto	T.					
T. Drinkard		. T. Delawar	e Sand	Τ.	Entrada	T.					
Т. Аво	6914	T. Bone Sp	rings	T.	Wingate						
T. Wolfcamp	7808	r. Virg		<u>5</u> т.	Chinle	T.					
T. Penn.		T. Bough	1 D 024	<u>4</u> T	Permian	T.					
T Cisco (Bough C) _	8432	T. Bough	<u>n C 828</u>	<u>8</u> т.	Penn. ''A''	T.					
			OIL OR	GAS SA	ANDS OR ZONES						
No. 1, from		to		No	. 4, from		to				
No. 2, from	·	to	······	Nc	5, from	*** : • • • • • • • • • • • • • • • •	to				
No. 3, from		to		No	No. 6, from						
IMPORTANT WATER SANDS											
Include data on rate of water inflow and elevation to which water rose in hole.											
No. 1, from			to		feet	*******					
No. 2, from			to		feet	feet					
No. 3, from			to		feet						
No. 4, from			to		feet	••-•					

FORMATION RECORD (Attach additional sheets if necessary)

From	То	Thickness in Feet	Formation	From	То	Thickness in Feet	Formation
0	45	45	Surface Rock, Redbeds				
45	1791	1746	Redbeds				
1791	2157	366	Redbeds, Anhydrite, Salt				
2157	3520	1363	Anhydrite, Salt Stringers				
3520	4260	740	Dolomite, Anhydrite				
4260	4416	156	Limestone				
4416	4580	164	Limestone, Dolomite				
4580	6430	1850	Dolo, Anhy, Sand, Shale				
6430	6926	496	Dolo, Anhy, Sd, Shale, Li	ne			
6926	7540	614	Shale				
7540	7820	280	Shale, Dolomite				
7820	8480	660	Shale, Lime				