

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Burgland "AAG"
Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 1
Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 14 TOWNSHIP 7S RANGE 33E NMPM.	10. Field and Pool, or Wildcat No. Chaverro-Permo Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4371' GR	12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER ☒ Production Csg., Perforate, Treat

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1105.

TD 8480'. Ran 202 jts 5-1/2" 15.5# and 17# casing set 8480' as follows: 39 jts 17# J-55; 162 jts 15.50# J-55 and 1 jt 17# J-55. Regular cement guide shoe set 8480'. Super seal float collar set 8442'. Cemented w/300 sacks Class "H" .6% CF-1 and 2% KCL. Compressive strength of cement - 850 psi in 12 hrs. PD 12:00 AM 10-19-84. Bumped plug to 1000 psi for 30 minutes, released pressure, float and casing held okay. WOC 18 hrs. WH and perforated 8246-62' w/15 .45" holes as follows: 8246, 47, 49, 51, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62 and 63'. Acidized perforations 8246-62' w/3500 gals NEFE acid. Swabbing back load.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed <u>Jerry Sexton</u>	TITLE <u>Production Supervisor</u>	DATE <u>11-1-84</u>
ORIGINAL SIGNED BY JERRY SEXTON		
PROVED BY <u>DISTRICT SUPERVISOR</u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		

NOV - 5 1984