

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-76

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
NO. OF	
DATE OF FILE	
OPERATOR	

5c. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒

GAS WELL ☐

OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM West LINE, SECTION 14 TOWNSHIP 7S RANGE 33E NMPL.

7. Unit Agreement Name

8. Farm or Lease Name
Burgland AAG

9. Well No.
1

10. Field and Pool, or Wildcat
North Chaverro-Permo Penn

15. Elevation (Show whether DF, RT, GR, etc.)

4371' GR

12. County

Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☐

OTHER Intermediate Casing ☒

OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3500'. Ran 87 joints of 8-5/8" 32# and 24# K-55 ST&C casing as follows: 39 joints of 8-5/8" 32# K-55 ST&C and 48 joints of 8-5/8" 24# K-55 ST&C (total 3503') set 3500'. 1-Texas Pattern notched guide shoe set 3500'. Super Seal float collar set 3459'. Cemented w/1000 sacks Pacesetter Lite, 6# salt/sack. Tailed in w/150 sacks Class "C" 1% CaCl₂. Compressive strength of cement - 850 psi in 12 hours. PD 4:00 PM 4-26-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 30 sacks. WOC. Drilled out 10:00 AM 9-27-84. WOC 18 hours. Nipped up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie W. Seay

TITLE Production Supervisor

DATE 10-16-84

Eddie W. Seay

PROVED BY Oil & Gas Inspector

TITLE

DATE

OCT 22 1984

CONDITIONS OF APPROVAL, IF ANY: