

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

C.L. CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☐	Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL ☐ GAS ☐ OTHER ☐ PSA		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Name of Leaseholder Tom Tucker "ACY"
3. Address of Operator 207 South 4th St., Artesia, NM 88210		9. Well No. 1
4. Location of Well UNIT LETTER <u>K</u> , <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>10</u> TOWNSHIP <u>7S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or wildcard No. Chaveroo Permo Penn
11. Elevation (Show whether DF, RT, GR, etc.) 4384.5 GR		12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☐	PLUG AND ABANDONMENT ☒
FULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Received verbal permission 11-16-85 from Jerry Sexton, NMOC, Hobbs to plug and abandon well as follows:

TD 9260'.

Plug #1: 9136-9036' with 30 sx Class "C" - Mississippian.
PD 11:57 PM 11-16-85.

Plug #2: 8307-8207' with 42 sx Class "C". PD 1:07 AM 11-17-85.

Plug #3: 7855-7755' with 42 sx Class "C" with 2% CaCl₂ - Wolfcamp Lime. PD 2:00 AM 11-17-85.

Plug #4: 4633-4533' with 55 sx Class "C" with 2% CaCl₂ - Glorieta. PD 6:20 AM 11-17-85.

Plug #5: 3546-3446' with 40 sx Class "C" with 2% CaCl₂ - 8-5/8" casing shoe. PD 7:45 AM 11-17-85.

Plug #6: 1912-1812' with 30 sx Class "C" with 2% CaCl₂ - Rustler Anhydrite. PD 9:35 AM 11-17-85.

Plug #7: 62'-Surface with 10 sx Class "C" with 2% CaCl₂. PD 11:00 AM 11-17-85.

Cut off wellhead and installed dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James A. Goodlett TITLE Production Supervisor DATE 11-20-85
APPROVED BY Jack Griffin TITLE OIL & GAS INSPECTOR DATE JUL 18 1986
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

NOV 22 1985

6 11-1
HORE 1 11-12