

Cementer: Fill in shaded areas.  
Operator: Fill in other items.

RAILROAD COMMISSION OF TEXAS  
Oil and Gas Division

1. Operator's Name (As shown on Form P-5, Organization Report) <b>Layton Enterprises</b>	2. RRC Operator No.	3. RRC District No.	4. County of Well Site <b>Roosevelt</b>
5. Field Name (Wildcat or exactly as shown on RRC records) <b>Alvarado Penn</b>	6. API No. <b>30-01-20197</b>		7. Drilling Permit No.
8. Lease Name <b>El Zorro Fed</b>	9. Rule 37 Case No.	10. Oil Lease/Gas ID No. <b>NH 53389</b>	11. Well No. <b>1</b>

CASING CEMENTING DATA:		SURFACE CASING	INTER-MEDIATE CASING	PRODUCTION CASING		MULTI-STAGE CEMENTING PROCESS	
				Single String	Multiple Parallel Strings	Tool	Shoe
12. Cementing Date		10-25-85	11-2-85	11-25-85			
13. •Drilled hole size		17½	11	7⅞			
•Est. % wash or hole enlargement							
14. Size of casing (in. O.D.)		13⅞	8⅞	5½			
15. Top of liner (ft.)							
16. Setting depth (ft.)		337	4120	9700			
17. Number of centralizers used		3	6	8			
18. Hrs. waiting on cement before drill-out							
1st Slurry	19. API cement used: No. of sacks ▶	350	1270	1025			
	Class ▶	C	HLH	H			
	Additives ▶	2% CC	15# Salt ½# Flo	Neat Foamed			
2nd Slurry	No. of sacks ▶		200	175			
	Class ▶		C	H			
	Additives ▶		2% CC	50/50 Poz 2% Gel 6# Salt			
3rd Slurry	No. of sacks ▶						
	Class ▶						
	Additives ▶						
1st	20. Slurry pumped: Volume (cu. ft.) ▶	462	2578	1210			
	Height (ft.) ▶	665	10141	6984			
2nd	Volume (cu. ft.) ▶		264	226			
	Height (ft.) ▶		1039	1304			
3rd	Volume (cu. ft.) ▶						
	Height (ft.) ▶						
Total	Volume (cu. ft.) ▶	462	2842	1436			
	Height (ft.) ▶	665	11180	8288			
21. Was cement circulated to ground surface (or bottom of cellar) outside casing?		Yes	Yes	No			
22. Remarks							

OVER

CEMENTING TO PLUG AND ABANDON	PLUG # 1	PLUG # 2	PLUG # 3	PLUG # 4	PLUG # 5	PLUG # 6	PLUG # 7	PLUG # 8
23. Cementing date								
24. Size of hole or pipe plugged (in.)								
25. Depth to bottom of tubing or drill pipe (ft.)								
26. Sacks of cement used (each plug)								
27. Slurry volume pumped (cu. ft.)								
28. Calculated top of plug (ft.)								
29. Measured top of plug, if tagged (ft.)								
30. Slurry wt. (lbs/gal)								
31. Type cement								

CEMENTER'S CERTIFICATE: I declare under penalties prescribed in Sec. 91.143, Texas Natural Resources Code, that I am authorized to make this certification, that the cementing of casing and/or the placing of cement plugs in this well as shown in the report was performed by me or under my supervision, and that the cementing data and facts presented on both sides of this form are true, correct, and complete, to the best of my knowledge. This certification covers cementing data only.

Larry D. Mensch Cementer Halliburton Services Larry D. Mensch  
Name and title of cementer's representative Cementing Company Signature  
P.O. Box 1108 Brownfield, Texas 79316 806-637-3591 12-6-85  
Address City, State, Zip Code Tel.: Area Code Number Date: mo. day yr.

OPERATOR'S CERTIFICATE: I declare under penalties prescribed in Sec. 91.143, Texas Natural Resources Code, that I am authorized to make this certification, that I have knowledge of the well data and information presented in this report, and that data and facts presented on both sides of this form are true, correct, and complete, to the best of my knowledge. This certification covers all well data.

DONALD R. LAYTON PRESIDENT Donald R. Layton  
Typed or printed name of operator's representative Title Signature  
2103 79th St. Lubbock, Tx. 79423 806-745-4638 12-10-85  
Address City, State, Zip Code Tel.: Area Code Number Date: mo. day yr.

### Instructions to Form W-15, Cementing Report

**IMPORTANT:** Operators and cementing companies must comply with the requirements of the Commission's Statewide Rules 8 (Water Protection), 13 (Casing, Cementing, Drilling, and Completion), and 14 (Well Plugging). For offshore operations, see the requirements of Rule 13 (c).

**A. What to file.** An operator should file an original and one copy of the completed Form W-15 for each cementing company used on a well. The cementing of different casing strings on a well by one cementing company may be reported on one form. Form W-15 should be filed with the following:

- An initial oil or gas completion report, Form W-2 or G-1, as required by Statewide or special field rules;
- Form W-4, Application for Multiple Completion, if the well is a multiple parallel casing completion; and
- Form W-3, Plugging Record, unless the W-3 is signed by the cementing company representative. When reporting dry holes, operators must complete Form W-15, in addition to Form W-3, to show any casing cemented in the hole.

**B. Where to file.** The appropriate Commission District Office for the county in which the well is located.

**C. Surface casing.** An operator must set and cement sufficient surface casing to protect all usable-quality water strata, as defined by the Texas Department of Water Resources, Austin. Before drilling a well in any field or area in which no field rules are in effect or in which surface casing requirements are not specified in the applicable rules, an operator must obtain a letter from the Department of Water Resources stating the protection depth. Surface casing should not be set deeper than 200 feet below the specified depth without prior approval from the Commission.

**D. Centralizers.** Surface casing must be centralized at the shoe, above and below a stage collar or diverting tool, if run, and through usable-quality water zones. In nondeviated holes, a centralizer must be placed every fourth joint from the cement shoe to the ground surface or to the bottom of the cellar. All centralizers must meet API specifications.

**E. Exceptions and alternative casing programs.** The District Director may grant an exception to the requirements of Statewide Rule 13. In a written application, an operator must state the reason for the requested exception and outline an alternate program for casing and cementing through the protection depth for strata containing usable-quality water. The District Director may approve, modify, or reject a proposed program. An operator must obtain approval of any exception before beginning casing and cementing operations.

**F. Intermediate and production casing.** For specific technical requirements, operators should consult Statewide Rule 13 (b) (3) and (4).

**G. Plugging and abandoning.** Cement plugs must be placed in the wellbore as required by Statewide Rule 14. The District Director may require additional cement plugs. For onshore or inland wells, a 10-foot cement plug must be placed in the top of the well, and the casing must be cut off three feet below the ground surface. All cement plugs, except the top plug, must have sufficient slurry volume to fill 100 feet of hole, plus ten percent for each 1,000 feet of depth from the ground surface to the bottom of the plug.

To plug and abandon a well, operators must use only cementers approved by the Director of Field Operations. Cementing companies, service companies, or operators can qualify as approved cementers by demonstrating that they are able to mix and pump cement in compliance with Commission rules and regulations.