

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
N. M. OIL FUNDS COMMISSION  
SUBMIT IN THIS MANNER  
FOR OTHER INSTRUCTIONS  
VERSE MILEY  
HOBBS, NEW MEXICO 88240

Budget Bureau No. 1004-0135  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐  
2. NAME OF OPERATOR  
MURPHY OPERATING CORPORATION  
3. ADDRESS OF OPERATOR  
P. O. Drawer 2648, Roswell, NM 88202-2648  
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface  
1980' FSL & 1980' FWL, Section 29, T7S, R36E

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Todd Lower S/A Unit

8. FARM OR LEASE NAME

Todd Lower S/A Ut. Sec. 29

9. WELL NO.

32 //

10. FIELD AND POOL, OR WILDCAT

Todd Lower S/A Assoc.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 29, T7S, R36E

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

4141' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) cement surface casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud well at 3:30 p.m. MST July 24, 1988. Ran 2016' (48 joints) of 8-5/8" 24# J-55 ST&C casing and set at 2014'. Cement with 750 sacks Howcolite, 10#/sack salt, & 1/4#/sack Flocele. Tail in with 200 sacks Class C cement with 2% CaCl. Circulated 200 sacks cement to pit. Plug down @ 9:30 p.m. MST July 25, 1988.



18. I hereby certify that the foregoing is true and correct

SIGNED Melinda K. Hickman

TITLE Production Supervisor

DATE August 15, 1988

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
DATE  
PETER W. CHESTER

AUG 23 1988

\*See Instructions on Reverse Side