rm 3160-5 ovember 1983)	UNITED STATES "	A BAX 9980 Instructions	re Expires August 31, 1985 5. LEASE DESIGNATION AND SEBIAL NO.
ormerly 9-331) UEPA	ARTMEN. OF THE INTE JREAU OF LAND MANAGEME	BBS, NEW MEXICO 8824	10 NM-0321281
			6. IF INDIAN, ALLOTTEE OF TRIBE NAME
(Do not use this form for	NOTICES AND REPORTS proposals to drill or to deepen or plu PPLICATION FOR PERMIT—" for suc	b ON WELLS ig back to a different reservoir. h proposals.)	
			7. UNIT AGREEMENT NAME
OIL GAS OTHER		Todd Lower S/A Unit	
NAME OF OPERATOR		8. FARM OR LEASE NAME	
MURPHY OPERATING CO	ORPORATION		Todd Lower S/A Ut. Sec
ADDRESS OF OPERATOR			9. WELL NO.
P. O. Drawer 2648, Roswell, New Mexico 88202-2648 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)		12 -	
		10. FIELD AND POOL, OR WILDCAT	
At surface			Todd Lower S/A Assoc. 11. BEC., T., B., M., OB BLK. AND
Unit Letter K, 1980' FSL & 710' FWL, Section 29, T7S, R36E		BURVEY OR AREA	
Unit Letter K, 1980)' FSL & /10' FWL, Sect	ion 29, 175, R36E	
	1 15. ELEVATIONS (Show whethe	TOP DT (D ata)	Sec. 29, T7S, R36E 12. COUNTY OB PABISE 13. STATE
PERMIT NO.			Roosevelt New Mexi
	4143' GR, 4155		I ROOSEVEIL New MEXI
Chee	ck Appropriate Box To Indicate	e Nature of Notice, Report, (or Other Data
	INTENTION TO :		BEEQUENT REPORT OF :
I VOLICE OF			
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTEBING CASINO
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	roduction casing X
REPAIR WELL	CHANCE PLANS		suits of multiple completion on Well
(Other)	<u> </u>		completion Report and Log form.) lates, including estimated date of starting as
April 3, 1988 - TD at 4399' KB. Cemer	4400' KB. Ran 4407' (nt with 500 gals. mud f	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s	.5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack
April 3, 1988 - TD at 4399' KB. Cemer Flocele, 5#/sack G	4400' KB. Ran 4407' (nt with 500 gals. mud f	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	.5.5# J-55 ST&C casing and a
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	.5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	.5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	.5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	.5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack k salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack k salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack k salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack k salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack k salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack k salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	5.5# J-55 ST&C casing and s sacks Howcolite, 1/4#/sack k salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack k salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug	4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	5.5# J-55 ST&C casing and s sacks Howcolite, 1/4#/sack k salt. Circulated 410
nent to this work.)* April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug API No. 20378.	directionally drilled, give subsurface 4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s g down @ 3:30 p.m. MST	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	5.5# J-55 ST&C casing and s sacks Howcolite, 1/4#/sack k salt. Circulated 410
nent to this work.)* April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Pluy API No. 20378.	directionally drilled, give subsurface 4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s g down @ 3:30 p.m. MST going 1s true and correct	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac	5.5# J-55 ST&C casing and stacks Howcolite, 1/4#/sack ek salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug API No. 20378.	directionally drilled, give subsurface 4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s g down @ 3:30 p.m. MST g down @ 3:30 p.m. MST TITLE_	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac April 3, 1988.	5.5# J-55 ST&C casing and s sacks Howcolite, 1/4#/sack ek salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Pluy API No. 20378.	directionally drilled, give subsurface 4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s g down @ 3:30 p.m. MST g down @ 3:30 p.m. MST TITLE_ TITLE_ TITLE_ TATE office vse)	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac April 3, 1988.	5.5# J-55 ST&C casing and s sacks Howcolite, 1/4#/sack sk salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Pluy API No. 20378.	directionally drilled, give subsurface 4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s g down @ 3:30 p.m. MST going is trie and correct 	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac April 3, 1988.	5.5# J-55 ST&C casing and s sacks Howcolite, 1/4#/sack ek salt. Circulated 410
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug API No. 20378.	directionally drilled, give subsurface 4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s g down @ 3:30 p.m. MST going is trie and correct 	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac April 3, 1988.	Dr DATE April 18, 198
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Pluy API No. 20378.	directionally drilled, give subsurface 4400' KB. Ran 4407' (nt with 500 gals. mud f ilsonite. Tail: 250 s g down @ 3:30 p.m. MST going is trie and correct 	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac April 3, 1988.	Dr DATE April 18, 198
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Pluy API No. 20378.	directionally drilled, give subsurface 4400' KB. Ran 4407' (nt with 500 gals. mud fi ilsonite. Tail: 250 s g down @ 3:30 p.m. MST going is true and correct 	Production Supervise	APR 2 0 1988
April 3, 1988 - TD at 4399' KB. Cemen Flocele, 5#/sack G sacks to pit. Plug API No. 20378.	directionally drilled, give subsurface 4400' KB. Ran 4407' (nt with 500 gals. mud fi ilsonite. Tail: 250 s g down @ 3:30 p.m. MST going is true and correct 	(106 joints) 5-1/2" 1 Elush. Lead: 1250 s sacks Class H, 5#/sac April 3, 1988.	Dr DATE April 18, 198

-

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make totally department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

