

UNITED STATES N. M. OIL & GAS COMMISSION  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
HOBBS, NEW MEXICO 88240

Budget Bureau No. 1004-0135  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-0139989A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR  
MURPHY OPERATING CORPORATION

3. ADDRESS OF OPERATOR  
P. O. Drawer 2648, Roswell, NM 88202-2648

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1780' FSL & 1980' FWL, Section 30, T7S, R36E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4146 GR, 4158 KB

7. UNIT AGREEMENT NAME

Todd Lower S/A Unit

8. FARM OR LEASE NAME

Todd Lower S/A Ut. Sec. 30

9. WELL NO.

11

10. FIELD AND POOL, OR WILDCAT

Todd Lower S/A Assoc.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 30, T7S, R36E

12. COUNTY OR PARISH 13. STATE

Roosevelt New Mexico

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) cement production casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

April 13, 1988 - TD 4400'. Ran 4416' (101 joints) 5-1/2", 15.5#, J-55 ST&C casing and set at 4395' KB. Cement with 500 gals. mud flush. Lead: 1250 sacks Howcolite, 1/4#/sack Flocele, and 5#/sack Gilsonite. Tail: 250 sacks Class H, 5#/sack salt. Circulated 410 sacks to pit. Plug down @ 11:15 a.m. MST April 13, 1988.

RECEIVED  
MAY 3 8 22 AM '88  
BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA

19. I hereby certify that the foregoing is true and correct

SIGNED

Melinda K. Hickman  
Melinda K. Hickman

TITLE Production Supervisor

DATE May 2, 1988

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
PETER W. CHESTER

DATE

MAY 9 1988

BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA

\*See Instructions on Reverse Side

RECEIVED

MAY 10 1968

CC  
MAY 10 1968