

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
N. M. OIL CONS. COMMISSION
HOBBS, NEW MEXICO 88240

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-0139989A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Todd Lower S/A Unit

8. FARM OR LEASE NAME

Todd Lower S/A Ut. Sec. 30

9. WELL NO.

11

10. FIELD AND POOL, OR WILDCAT

Todd Lower S/A Assoc.

11. SEC. T. R. M. OR BLK. AND SURVEY OR AREA

Sec. 30, T7S, R36E

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
MURPHY OPERATING CORPORATION

3. ADDRESS OF OPERATOR
P. O. Drawer 2648, Roswell, NM 88202-2648

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1780' FSL & 1980' FWL, Section 30, T7S, R36E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

4146 GR, 4158 KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PCLL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) cement surface casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well at 1:15 p.m. MST April 4, 1988. Ran 409' (10 joints) of 8-5/8" 24# J-55 ST&C casing and set at 408' (KB). Cement with 250 sacks Class C cement with 2% CaCl 1/4#/sack salt. Circulated 35 sacks cement to pit. Plug down @ 7:00 p.m. MST April 4, 1988.

18. I hereby certify that the foregoing is true and correct

SIGNED

Melinda K. Hickman

TITLE Production Supervisor

DATE May 2, 1988

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED
MAY 3 8 23 AM '88
BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

ACCEPTED FOR RECORD
PETER W. CHESTER
DATE
MAY 9 1988
BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA