

Form 100-1
November 1987
For use by BLM

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
HOBBS, NEW MEXICO 88240

Form approved
Budget Bureau No. 1004-111-0
Expires August 31, 1989

5. LEASE DESIGNATION AND SERIAL NO.
NM 57700
6. IF INDIAN ALLOTTEE OR TRIBE NAME

SUMMARY NOTICES AND REPORTS ON WELLS

1. This form is to be used for proposals to drill or to deepen or plug back to a different reservoir.
(See APPLICATION FOR PERMIT for such proposals.)

2. NAME OF OPERATOR
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR
105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

330' FSL & 990' FEL, Sec. 22-T7S-R35E

14. PERMIT NO.
API #30-041-20841

15. ELEVATIONS (Show whether DE, RT, GR, etc.)
4194.6' GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Crossroads AFX Federal

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA
Unit P, Sec. 22-T7S-R35E

12. COUNTY OR PARISH
Roosevelt

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Perforate, Treat

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

1-27-89. Perforated 7963-7972' w/10 .50" holes. Acidized perforations 7963-7972' w/
1500 gals 20% NEFE acid and 8 ball sealers.

1-31-89. Set CIBP 7920' w/35' cement cap on top. Perforated 7652-7657' w/6 .50"
holes. Acidized perforations 7652-7657' w/1000 gals 20% NEFE acid and 3 ball sealers.

2-4-89. Set cement retainer at 7642'. Cemented w/150 sx Class H cement with fluid
loss additive, 105 sacks in formation. Squeezed perfs 7652-57' to 3500 psi. Reversed
hole clean.

2-6-89. WIH and perforated 7594-7597' and *7610-7616' w/11 .50" holes (1 SPF).
Acidized perforations w/1500 gals 20% NEFE acid and 8 ball sealers. Swabbing well.

AMENDED REPORT TO SHOW PERFORATIONS 7610-7616'.

18. I hereby certify that the foregoing is true and correct

SIGNED *Wanda Swadlow*

TITLE Production Supervisor

DATE 2-17-89

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

MAR 14 1989

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the
United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.