

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. ~~Anhy~~ Rustler 2094
T. Salt _____
B. Salt _____
T. Yates 2358
T. 7 Rivers _____
T. Queen _____
T. Grayburg _____
T. San Andres 3482
T. Glorieta 4804
T. ~~Padlock~~ CLEARFORK 5449
T. Blinebry _____
T. Tubb 6100
T. Drinkard _____
T. Abo 6865
T. Wolfcamp 7480
T. Penn _____
T. Cisco (Bough C) 8072

T. Canyon _____
T. Strawn _____
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian 8260
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Delaware Sand _____
T. Bone Springs _____
T. Cambrian 8524
T. Precambrian 8567
T. _____
T. _____

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Otzte _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	40	40	Surface, Rock				
40	3300	3260	Redbeds, Salt, Anhy				
3300	3380	80	Sh, Anhy				
3380	3886	506	Sh, Sd, Anhy				
3886	4418	532	Dolo, Anhy, Sh				
4418	4680	262	LS, Dolo				
4680	4810	130	LS, Dolo, Anhy				
4810	5912	1102	LS,Dolo, Anhy, Sh, Sd				
5912	6800	888	Dolo, Anhy, Sh, Sd				
6800	7040	240	Anhy, Sh				
7040	7260	220	Sh				
7260	7400	140	Sh, Anhy				
7400	7600	200	Dolo				
7600	7756	156	Dolo, Cht				
7756	8252	496	LS, Sh				
8252	8700	448	Dolo, Cht				