APPLICATION TO DRILL

PLAINS PETROLEUM OPERATING COMPANY BLUITT SAN ANDRES UNIT, WELL NO. 1301 660' FN&EL, SEC. 13, T8S, R37E ROOSEVELT COUNTY, NEW MEXICO LEASE NO.: 044216

In conjunction with Form 3160-3, Application to Drill above well, Plains Petroleum Operating Company submits the following in accordance with BLM requirements.

1. The estimated tops of geological markers are: Surface Elevation:

5 - San

Formation	Depth (Top)	Fluid Content
San Andres	3850'	
Pi Marker	4350'	
P ₁	4460'	Gas
P ₂	4600'	Oil
P ₃	4700'	Brine
P ₃	4700'	Brine

or 13#

- 2. <u>Casing Program</u>: (A) Surface Casing 8-5/8" 20# X42 used inspected (B) Production Casing 5-1/2" 14# J-55 used inspected
- 3. <u>Cementing Program</u>: (A) 8-5/8" csg set at 350° +. Cemented to surface with 225 sx of Premium Plus 2% C₂C₂.
 - (B) 5-1/2" csg set at 4800'+. Cemented to surface with 875 sx Halliburton Lite with 1/4# flocele & 15 lbs salt; followed by 225 sx Class "A" 50-50 pozmix, 5# salt/sk, 2% Gel.
- 4. <u>Mud Program</u>: $0 \frac{250^{\circ}}{350^{\circ}}$ Spud mud, FW, Gel 350'- 4500' Brine & native mud, mud at 9.4-10.2 ppg, vis. 32-40 SW for logs.