

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
HOBBS, NEW MEXICO 88240
P.O. BOX 1980

ND60-3160-4
5. LEASE DESIGNATION AND SERIAL NO.
NM-044216
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR EXPLORATION" for such proposals.)

1. NAME OF OPERATOR Plains Petroleum Operating Co.	4. ASSESS CODE & PHONE NO. (915) 683-4434	7. UNIT ACROSS OF LAND Bluitt San Andres Unit Sec.18
3. ADDRESS OF OPERATOR 415 West Wall Street, Suite 2110 Midland, Texas 79701		8. BIRTH OR LEASE DATE
2. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. E.g. "Sec. 18, T8S, R3E, E1/4") Unit Letter K - 1980 FSL, 1980 FWL		9. WELL NO. 1841 14 11
		10. FIELD AND POOL, OR WILDCAT Bluitt San Andres
		11. SEC., T., R. OR BLM. AND BUREAU OR AREA Sec.18, T8S, R3E
12. PERMIT NO.	13. DEPTH (State whether DF, RT, or, etc.) 3986.5' GR	14. COUNTY OR PARISH Roosevelt
		15. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
PRODUCTION MAX	☐	PRODUCTION MAX	☐
PRODUCTION MIN	☐	PRODUCTION MIN	☐
PRODUCTION	☐	PRODUCTION	☐
(Other)	☐	(Other)	☐

17. Describe the nature of the notice, report, or other data (Specify the type of notice, report, or other data and give pertinent dates, including estimated date of starting any production, if well is shut-in, give the shut-in date and measure and time required to shut-in the well and give production to date work.)

4-26-90 Norton Drilling Co. spudded 12-1/2" hole. Ran 12 jts 8-5/8" 20# X42 STAC csg w/ notched Texas pattern shoe (total 510.32'), insert baffle and 4 centralizers @ 484', 404', 324' and 244'. Set csg w/landing jt @ 524' KB. Cased w/310' sm Class "C" w/2% CaCl₂, circ 74 ex out to surface of. Tested 60' @ 3000 psi, held OK.

5-5-90 Drig 7-7/8" hole @ 48' KB. Ran 112 jts 5 1/2" 14# J55 STAC csg set @ 4940' KB, 5-1/2" guide shoe & shoe jt 44.15' and insert float. Ran centralizers @ 4918', 4852', 4764', 4676', 4587', 4499', 4411', 4323', 4234' and 4143'. Top of short marker jt @ 4521.27' KB. Pumped 100 181 lb followed by 1200 ex Premium plus 32 Ecorolite w/6% salt/sack & 1/2" Floccul/sack tailed in w/200 ex Premium plus neat. Circ 186 ex out to surface. WOC

18. I hereby certify that the foregoing is true and correct

SIGNED Stephen D. Owen TITLE Operations Engineer DATE 5-8-90

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

