

Continued, Sundry Notices and Reports on Wells

10-6-93 Ran 95 jts (3907') 8-5/8" 32# J-55 csg @ 3902' wt w/1325 sx Class C-lite w/5# salt + 1/4# Celloflake @ 12.5 ppg and 200 sx Class C w/2% CaCl @ 14.8 ppg.

10-17-93 Drill w/bottom hole motor & 1-1/4 Bent Sub to get bottom hole
thru location back on Devonian proration unit. Top of Devonian bottom
10-22-93 hole location is 1.28' N & 56.9' E of surface location.

10-31-93 Ran 239 jts (9090.07) 5 1/2" 20 & 17# N-80 & K-55 LT&C @ 9035'.
Cemented w/510 sx H-lite w/0.2% sodium metasilicate @ 12.4 ppg F/B
250 sx H w/0.2% sodium metasilicate, 1% BA-58, 1% F1-62, 0.3% CD 32
& 0.3% r-3 @ 15.6 ppg.

11-6-93 Perf 8926-33' w/4 jspf (32 holes).

11-10-93 TIH w/5 1/2" cmt retainer (Baker K-1; same as Halliburton E-Z Drill)
& set @ 8920'. Cmt locked up w/14 bbls below retainer.

11-11-93 Perf @ 8834-42', 8852-54' & 8862-65' w/4 jspf.

12-8-93 Baker cmt Ret. Set @ 8794'.

12-9-93 Sqz Devonian perms w/100 sx Class H neat cmt. Spot 3 sx cmt on top
of ret. Perf Wolfcamp @ 7945, 49, 51, 56, 58, 62, 64, 67, 69, 71 &
74 w/4 jspf w/csg gun.

1/9/94 Potential Test: CAOF 1.552 MCFD.

