

STRATA PRODUCTION COMPANY

P.O. BOX 1030

ROSWELL, N.M. 88202

WELL PROGRAM

WELL NAME: ALONDRA #1

A.F.E. No: A-7-34-17-1L

LOCATION: NW/SW SECTION 17-T7-R34E, ROOSEVELT COUNTY, N.M.
DIRECTIONS: WEST OF MILNESAND 5 MILES, NORTH 1 MILE, WEST 3 MILES, NORTH 3 MILES
WEST 0.8 MILES, NORHT 1/4 MILE TO LOCATION.

ELEVATION: 4315' (EST.) K.B.: 4330' (EST.)

FORMATIONS	DEPTH	SUBSEA	FORMATIONS	DEPTH	SUBSEA
RUSTLER ANHY.	1930	2400	ABO	7030	-2700
SALADO (SALT)	1950	2380	WOLFCAMP	7960	-3630
YATES	2225	2105	CISCO	8470	-4140
SAN ANDRES	3360	970	MISSISSIPPIAN	8950	-4620
YESO	4700	-370	SILURO-DEVONIAN	9400	-5070
TUBB	6180	-1850	T.D.	9600	-5270

SAMPLES: 10' SAMPLES FROM INTERMEDIATE CASING TO T.D.
DRLG. TIME: 1 FOOT DRLG. TIME BY GEOLOGRAPH FROM INTERMEDIATE CASING TO T.D.
LOGS: GR-CNL-LDT INT. TO T.D., GR-CNL SURF. TO T.D., GR-DLL-MSFL-S.P.-
SONIC INTERMEDIATE CASING TO T.D.
CORES: SIDEWALL CORES AS NEEDED
DST'S: THREE DRILL STEM TESTS- BOUGH A, B & C, WOLFCAMP AND DEVONIAN
REMARKS: MUD LOGGER ON FROM TOP OF ABO (7030') TO T.D.
DRILLING RIG:

CASING PROGRAM		BEARING SERVICE & SUPPLY ARTESIA, N.M. 505-746-9811				TORQUE
INTERVALS	LENGTH	CASING	BURST	COLLAPSE	TENSION	FT-LBS OPTIMUM
SURFACE						
0-350'	350	13 3/8 48# H-40, ST&C	1730	770	322,000	3220
INTERMEDIATE						
0-50'	50	8 5/8 32#J-55, LT&C	3930	2530	372,000	4520
50-2250'	2200	8 5/8 24#J-55, ST&C	2950	1370	244,000	2630
2250-3400'	1150	8 5/8 32#J-55, LT&C	3930	2530	372,000	4520

NOTE: SPECIAL DRIFT 32# FOR 7 7/8" BIT

PRODUCTION						
0-1600	1600	5 1/2" 17#, N-80, LT&C	7740	6280	348,000	3750
1600-7800'	6200	5 1/2" 17#, K-55, LT&C	5320	4910	272,000	2720
7800-9600	1800	5 1/2" 17#, N-80, LT&C	7740	6280	348,000	3750

RECEIVED

JUL 1 8 1995

JOHN HOBBS
OFFICE