

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.
30-041-20888

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
VA-1297

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Bluitt "16" State

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
OGS Operating Co., Inc.

8. Well No.
2

3. Address of Operator
550 W. Texas, Suite 1140, Midland, TX 79701

9. Pool name or Wildcat
Bluitt, San Andres Assoc.

4. Well Location
Unit Letter C : 660 Feet From The North Line and 1980 Feet From The West Line

Section 16 Township 8-S Range 37-E NMPM Roosevelt County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4027 GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Move in and rig up Rod Rig rig #2. Spud well @ 2:30 PM 10-5-99. Drilled 12 1/4" hole to 395'. Ran 8 5/8" 24# J-55 csg to 390' and cemented to surface with 225 sx Class "C" Cement on 10-5-99. Circ 52 sx cmt. WOC 12 hrs. Install wellhead and 11" 3000 psi double ram BOP. Test casing, BOP & choke manifold to 500 psi. Drilled 7 7/8" hole to 4712' and cemented around shoe with 265 sx 50/50 POZ "C" and thru DV tool at 1667' with 300 sx 35/65 POZ "C" and 100 sx Class "C" on 10-12-99. Rig down and move out rotary tools. Ran GR-CCL log thru casing on 10-22-99. Drilled to 4770' with reverse unit on 10-25-99. Acidized open hole interval from 4712' to 4770' with 2500 gal 15% HCL on 10-27-99. Fraced with 15000 gal gelled water and 26500# sand on 10-30-99. Ran 2 3/8" tubing to 4707' and flow back load water. Ran # point potential test on 11-30-99

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

James P. Phil Stinson

TITLE Agent for OGS Operating Co., Inc. DATE 12-13-99

TYPE OR PRINT NAME

James P. "Phil" Stinson

TELEPHONE NO. 915 682-6573

(This space for State Use)

ORIGINAL SIGNED BY

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: