

AUXILIARY EQUIPMENT

DRAWWORKS	BDW 650 HP, with Parmac Hydromatic brake
ENGINES	Two Caterpillar D-353 diesels rated at 425 HP each
ROTARY	Ideco 23", 300 ton capacity
MAST/SUB	Ideal 132', 550,000 lb. rated static hook load with 10 lines. Wagner 15' high substructure
TRAVELLING	Gardner-Denver, 300 ton, 5 sheave w/BJ 250 ton hook
EQUIPMENT	Brewster Model 7 SX 300 ton swivel
PUMPS	Continental-EMSCO DC-700 and DE-550, 5-1/2 X 16" Duplex, Compound driven.
PIT SYSTEM	1-Shale Pit 6X7X35', 1-Setting Pit 6X7X38', 1-Suction Pit 6X7X34' w/5 mud agitators, Two Centrifugal mud mixing pumps and a Double Screen Shale Shaker.
LIGHT PLANT	Two CAT 3306 diesel electric sets 18 KW prime power
BOP EQUIP.	11" 3000 psi WP double ram and 11" 3000 psi WP Shaffer Annular Preventer. Choke manifold rated at 3000 psi Valvcon 5-station 80 gallon closing unit.

Exhibit "D"
OGS Operating Co., Inc.
Bluitt "8" Fed #1
Section 8, T-8-S, R-37-E
Roosevelt County, New Mexico