

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-041-20898

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

VA 2382

7. Lease Name or Unit Agreement Name:

Bolero State

8. Well No. 1

9. Pool name or Wildcat

Bluitt Wolfcamp

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Primero Operating, Inc.

3. Address of Operator

PO Box 1433, Roswell, NM 88202-1433

4. Well Location

Unit Letter L : 1650 feet from the South line and 660 feet from the West line

Section 2

Township 8S

Range 37E

NMPM

Roosevelt

County

10. Elevation Show whether DR, RKB, RT, GR, etc.)

4050 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS.

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB

OTHER ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/22/02

Set CIBP @ 5080' and bailed 35' of cement on top

Set CIBP @ 3650' and bailed 35' of cement on top

Perforated 4 squeeze holes at 550' and pumped 35 sacks cement squeezing in and outside of 5 1/2" casing

Pumped 10 sx at 32'

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

We will install a dry hole marker, clear the location of junk, remove anchors and level location to NMOCD standards

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE President DATE 5/23/02

Type or print name Phelps White

Telephone No. 505-622-1001

(This space for State use)

APPROVED BY

TITLE

DATE JAN 09 2003

Conditions of approval, if any:

REPRESENTATIVE STATE MANAGER

GWW