

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease
Federal ☐ STATE ☐ FEE ☐

6. State Oil & Gas Lease No.
NM-8143012321 SLUP

7. Lease Name or Unit Agreement Name

Cato Seed

8. Well No. 5-B

9. Pool name or Wildcat
N/A

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☐ OTHER SWD

2. Name of Operator
MWJ PRODUCING COMPANY

3. Address of Operator
400 W. Illinois - Suite 1100 Midland, Texas 79701

4. Well Location
Unit Letter P : 660 Feet From The south Line and 660 Feet From The east Line
Section 5 Township 8S Range 30E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4030' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/12/90: MI & RU PU. Installed BOP & POOH w/249 jts 2-7/8" tbg.
9/13/90: RU Halliburton & pmpd 150 BFW. Ran & set Baker 5-1/2" CIBP @ 7940'.
Loaded csg w/50 BFW & circ w/9.5# mud. Set 20 sx cmt plug from
7940' to 7770'. Pulled & LD 111 jts tbg. With end of tbg @ 4351',
circ 9.5# mud & set 35 sx cmt plug from 4341' to 4191'. Pulled &
LD 74 jts tbg. With end of tbg @ 2041', circ w/9.5# mud & set 30 sx
cmt plug from 2041' to 1921'. Pulled & LD 41 jts tbg. With end
of tbg @ 788', circ w/9.5# mud & set 30 sx cmt plug from 788' to
688'. Pulled & LD 23 jts tbg. With end of of tbg @ 60', set 15 sx
cmt plug to surface.
9/14/90: Removed BOP & tbg head flange. RD & MO.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Pat Drexler TITLE Pat Drexler-Agent DATE 1/11/91

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use) **FOR RECORD ONLY**

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

JAN 15 1991