



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office N.M.
Lease No. 01127
Unit Hinkle

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT <input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 7, 1958

Well No. 1 is located 660 ft. from N line and 660 ft. from E line of sec. 15

N.W. 15 13 S 30 E. N.M.P.M.
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Chaves New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Plugged well in this manner: 7 7/8" hole filled with heavy mud and set 50' cement plug (16 sacks) from 3150' to 3100' and set 75' cement plug (24 sacks) from 2160' to 2085' and set 50' cement plug (16 sacks) from 1550' to 1500' and set 50' cement plug (16 sacks) from 750' to 700' and set 50' cement plug (16 sacks) from 385' to 335' using Halliburton Cementing Company, completed filling hole with heavy mud, set plug at surface with marker and cleaned location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company May HightowerAddress 503 West QuayArtesia, New Mexico

By May Hightower
Title Operator