

(SUBMIT IN TRIPLICATE)

Land Office N MLease No. 01129-15

Unit \_\_\_\_\_

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO <del>RE-ENTER</del> <u>REPAIR</u> WELL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE <input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 10

1977

Well No. 1 is located 1980 ft. from N line and 660 ft. from E line of sec. 21  
34 N 13 South 30 East Wilcox  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wilcox Chaves New Mexico  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3945 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-  
 This is well originally drilled and plugged by Gulf Oil Corporation.  
 Drilled 15715 ft. L.D. 2575 ft. of 9 5/8" casing set and cemented.  
 Intention to drill out top plug in 9 5/8" casing clean out to  
 the bottom plug in said casing approximately 2650 ft. Perforate  
 Queens sand between 2625 to 2225. Perforate San Andreas between  
 2600 and 2550 ft., and probably underflow both zones. Possibly  
 perforate Yates section between 1275 to 1420.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Clarence Angle  
3718-34th St.  
Lubbock, Texas  
 Address \_\_\_\_\_

By Clarence Angle

Title \_\_\_\_\_