## (SUBMIT IN TRIPLICATE)

Land Office Santa Fe

Unit Malco

UNITED STATES HORES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY** MED IN 24 M 9:45

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS.	 SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	 SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	 SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	 SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING.	 SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO ABANDON WELL.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  Way 14  [19]  Well No. B-1 is located 660 ft. from Nay line and 660 ft. from Nay line of sec.  NE/4 NE/4 of 14  15S  30E  N.M.P.M.  (K Sec. and Sec. No.)  (Typ.)  (Range)  (County or Subdivision)  The elevation of the derrick floor above sea level is ft.  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, certing points, and all other important proposed work)  We propose to drill a 12-1/4 hole to 200°, set and coment 8-5/8" at 200° with 100 sacks coment. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and coment with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company  MORRIS R. ANTWEIL		*****************		THE WEIGHT OF HATEK SHOT-OFF					
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO ABANDON WELL.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  Way 14.  [NOTICE OF INTENTION TO ABANDON WELL.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  Way 14.  [NOTICE OF INTENTION TO ABANDON WELL.  [NOTICE OF INTENTION TO ABAND	NOTICE OF INTENTION TO CHANGE PLA	NS	SUBSEQUI	ENT REPORT OF SHOOTING OR ACIDIZ	ING				
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO PULL OR ALTER CASING.  NOTICE OF INTENTION TO ABANDON WELL.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  Way 14.  19  Well No. B-1 is located 660 ft. from Notice of Report, NOTICE, OR OTHER DATA)  Well No. B-1 is located 660 ft. from Notice of Report, NOTICE, OR OTHER DATA)  Well No. B-1 is located 660 ft. from Notice of Report, NOTICE, OR OTHER DATA)  Well No. B-1 is located 660 ft. from Notice of Report, NOTICE, OR OTHER DATA)  Well No. B-1 is located 660 ft. from Notice of Report, NOTICE, OR OTHER DATA)  Well No. B-1 is located 660 ft. from Notice of Report, NOTICE, OR OTHER DATA)  Well No. B-1 is located 660 ft. from Notice of Report, NOTICE, OR OTHER DATA)  Well No. B-1 is located 660 ft. from Notice of Report, NOTICE, OR OTHER DATA)  (Graves Notice of Notice of Report, NOTICE, OR OTHER DATA)  Way 14	NOTICE OF INTENTION TO TEST WATER	SHUT-OFF	SUBSEQUI	ENT REPORT OF ALTERING CASING					
NOTICE OF INTENTION TO PULL OR ALTER CASING	NOTICE OF INTENTION TO RE-DRILL OF	REPAIR WELL	SUBSEQUI	SUBSEQUENT REPORT OF ABANDONMENT					
Well No. 2-1 is located 660 ft. from No. (Meridian)  Well No. 2-1 is located 660 ft. from No. (Meridian)  Well No. 3-1 is located ft. from No. 3-	NOTICE OF INTENTION TO SHOOT OR A	CIDIZE	SUBSEQUI						
Well No. B-1 is located 660 ft. from No. (Range) line and 660 ft. from No.	NOTICE OF INTENTION TO PULL OR ALT	TER CASING.	SUPPLEM						
Well No. B-1 is located 660 ft. from No. 14	NOTICE OF INTENTION TO ABANDON WE	E <b>LL</b>							
Well No. B-1 is located 660 ft. from No. 14									
Well No. 15 located 300 ft. from 15 line and 300 ft. from 15 line of sec.  NE/4 NE/4 of 14 158 30E N.M.P.M.  (% See, and Sec. No.) (Twp.) (Range) (Meridian)  Undesignated Chayes New Mexico  (Plot) (County or Subdivision) (State or Territory)  The elevation of the derrick floor above sea level is ft.  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cerling points, and all other important proposed work)  We propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company MORRIS R. ANTWEIL	(INDICATE	ABOVE BY CHECK MA	RK NATURE OF REF	PORT, NOTICE, OR OTHER DATA)					
NE/4 NE/4 of 14  15S  30E  N.M.P.M.  (3 See, and See, No.)  Undesignated  (Field)  (County or Subdivision)  The elevation of the derrick floor above sea level is  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cerling points, and all other important proposed work)  We propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company  NORRIS R. ANTWEIL				,					
NE/4 NE/4 of 14  15S  30E  N.M.P.M.  (26 Sec. and Sec. No.)  Undesignated  Chayes  (County or Subdivision)  The elevation of the derrick floor above sea level is  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, certing points, and all other important proposed work)  We propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company  DORRIS R. ANTWEIL	· ·			May 14	10 <b>56</b>				
Well No. 15 located 300 ft. from 15 line and 300 ft. from 15 line of sec.  NE/4 NE/4 of 14 158 30E N.M.P.M.  (% See, and Sec. No.) (Twp.) (Range) (Meridian)  Undesignated Chayes New Mexico  (Plot) (County or Subdivision) (State or Territory)  The elevation of the derrick floor above sea level is ft.  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cerling points, and all other important proposed work)  We propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company MORRIS R. ANTWEIL	1 221 16		. *************	<del></del>	, 17				
Well No. 15 located 300 ft. from 15 line and 300 ft. from 15 line of sec.  NE/4 NE/4 of 14 158 30E N.M.P.M.  (% See, and Sec. No.) (Twp.) (Range) (Meridian)  Undesignated Chayes New Mexico  (Plot) (County or Subdivision) (State or Territory)  The elevation of the derrick floor above sea level is ft.  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cerling points, and all other important proposed work)  We propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company MORRIS R. ANTWEIL	1. Jitacco 1		(NI)	( <b>E</b> )	7.4				
NE/4 NE/4 of 14  15S  30E  N.M.P.M.  (3 See, and See, No.)  Undesignated  (County or Subdivision)  Chaves  (County or Subdivision)  The elevation of the derrick floor above sea level is  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, certing points, and all other important proposed work)  The propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company  DORRIS R. ANTWEIL	Well No. 1 is located	d <b>660</b> ft. fro	m_xxx line a	and 660 ft. from war lin	ne of sec.				
Undesignated  Chayes  (County or Subdivision)  The elevation of the derrick floor above sea level is  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereing points, and all other important proposed work)  The propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company  MORRIS R. ANTWEIL			المار	TWT.					
Understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company    County or Subdivision				N.M.P.M.					
The elevation of the derrick floor above sea level isft.  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereing points, and all other important proposed work)  We propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate and of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced CompanyNORRIS R. ANTWEIL		(Twp.)	(Range)	(Meridian)					
The elevation of the derrick floor above sea level isft.  DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereing points, and all other important proposed work)  We propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate and of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced CompanyNORRIS R. ANTWEIL	Undesignated	Cha	YOR	New Mexic	0				
DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, certing points, and all other important proposed work)  We propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company  BORRIS R. ANTWEIL	(Field)	(Coun	ty or Subdivision)	(State or Terri	itory)				
DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, certing points, and all other important proposed work)  We propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company  BORRIS R. ANTWEIL			4173	1 .					
DETAILS OF WORK  (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, certing points, and all other important proposed work)  We propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company  BORRIS R. ANTWEIL	The elevation of the derrick fi	loor above sea	level is	ft.					
(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cereing points, and all other important proposed work)  The propose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate profit 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company  MORRIS R. ANTWEIL									
Tempose to drill a 12-1/4 hole to 200°, set and cement 8-5/8" at 200° with 100 sacks cement. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and cement with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company MORRIS R. ANTWEIL		DEL	AILS OF WO	ORK					
Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  **Company**  **Document**	(State names of and expected depths to o	bjective sands; show	sizes, weights, and	lengths of proposed casings; indicate	mudding jobs, cement-				
It 200° with 100 sacks coment. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and coment with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company MORRIS R. ANTWEIL		ing points, and a	n other important	proposed worky					
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced  Company  DORRIS R. ANTWEIL									
It 200° with 100 sacks coment. WOC 24 hours. Drill to approximate TD of 2900°, set 5-1/2" casing and coment with 125 sacks to test the Queen for production.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company MORRIS R. ANTWEIL	We recommon to deill	a 19_1/4 h	01a +0 90	301 met and seman	A 0 E/0"				
TD of 2900', set 5-1/2" casing and coment with 125 sacks to test the Queen for production.  1 understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced Company  BORRIS R. ANTWEIL	at 2001 with 100 mag	r coment	A PE JUAN	or, set and cemen	t 0-5/8"				
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced  Company MORRIS R. ANTWEIL	rn of 2000! got 5l	Manager.	TOC 24 E	ours. Drill to ap	proximate				
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced  Company	the Owen for product	'A" CERTHE	AND CHIEF	rat with 125 sacks	to test				
Company MORRIS R. ANTWEIL	rue desen for brodic	tron.							
Company MORRIS R. ANTWEIL									
Company MORRIS R. ANTWEIL									
Company MORRIS R. ANTWEIL									
Company MORRIS R. ANTWEIL				•					
Company MORRIS R. ANTWEIL									
Company MORRIS R. ANTWEIL									
Company MORRIS R. ANTWEIL									
Company MORRIS R. ANTWEIL									
D. O. D.— 3.0F0	I understand that this plan of work n	nust receive approval	in writing by the	Geological Survey before operations n	nay be commenced.				
D. O. D.— SOES	C	R. ANTWET	I.						
D. O. Roy 1058	Company								
A I I A A WA INIK AWAN	A 11 P. O. 1	Box 1058							
Address P. O. Box 1058	Address								

Hobbs, New Mexico Agent Title \_\_\_\_

U. S. GOVERNMENT PRINTING OFFICE 16-8487-5