

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR  
V. H. Westbrook

3. ADDRESS OF OPERATOR  
P. O. Box 2264

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660' FSL and 1980' FEL, Unit 0, Section  
AT SURFACE: 20, T-15-S, R-30-E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input checked="" type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)		

5. LEASE  
USA NM - 51837

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
-

7. UNIT AGREEMENT NAME  
-

8. FARM OR LEASE NAME  
Kinahan

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 20, T-15-S, R-30-E

12. COUNTY OR PARISH  
Lea County

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
GL-3994' KB 4008.2'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On 2/11/85, perforated at 9926' - 9939' with Schlumberger enerjet 1-11/16" tubing gun at 2 shots per foot. On 2/15/85, acidized with 2250 gallons of 7-1/2% morrow flo acid and 81,000 scf of nitrogen. The average rate was 5.2 BPM, the average pressure was 4625 psig, the instant shut-in pressure was 4100 psig and the 5 minute shut-in was 3700 psig. Recovered no gas or oil.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Pete Westbrook TITLE Manager DATE 4-20-85

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD DATE <u>PETER W. CHESTER</u>
APR 29 1985
BUREAU OF LAND MANAGEMENT ROSWELL RESOURCE AREA

RECEIVED  
MAY 1 1988  
C. C. C.  
HOBBS & CO.