

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLI
(Other instructions
reverse side)E*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND WELL NO.

New Mexico 8043
Special Land Use Permit
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Disposal Well		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR TEXACO Inc.		8. FARM OR LEASE NAME B. E. Spencer 'B' Fed.	
3. ADDRESS OF OPERATOR P. O. Box 728, Hobbs, New Mexico 88240		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FWL & 330' FWL of Sec. 28, T-15-S, R-30-E, Unit Letter D		10. FIELD AND POOL, OR WILDCAT Little Lucky Lake	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		12. COUNTY OR PARISH Chaves	
14. PERMIT NO. Regular		13. STATE N. M.	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4012' DF			

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2950' PBTD**1. Pull tubing and packer.****2. Run tubing, mud up hole, set cement retainer @ 2400' and
squeezeperforations from 2782-2450 w/100 ax. cement. Pull tubing.****3. Spot 10 ax. cement plug @ surface, install dryhole marker and clean
location.****See attached sketch for current condition of subject well.****RECEIVED**
JAN 7 1974
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

TITLE

Asst. Dist. Supt.

DATE

1-4-74

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

MAR 11 1974**H. L. BECK**
ARTESIA DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

• GPO 782-930

RECEIVED

MAR 12 1974

O. C. C.
ARTESIA, OFFICE

1 3/8" CSG. IN 1 7/2" HOLE
SET AT 469 CMT CIRC.

2 3/8" INTERNAL PLASTIC
COATED TBG AT 2400'

8 5/8" CSG IN 11" HOLE
SET AT 3000' W/1100 SX.

PACKED AT 2400'

PERFS. IN 8 5/8" CSG: 2450',
2513', 2590', 2593', 2615', 2629',
2644', 2658', 2669', 2694', 2702',
2706', 2716', 2755', 2772', 2780'

30 SX. PLUG 2950 - 3050

30 SX PLUG 4375 - 4475

7 7/8" OPEN HOLE
3000 - 11,353

30 SX. PLUG 6480 - 6580

RECEIVED

JAN 7 1974
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

30 SX PLUG 9750 - 9850

30 SX PLUG 11,180' - 11280'

T.D. 11,353

CURRENT CONDITION OF RE. SPENCER 'B' FEDERAL
WELL NO. 1

CHAVES COUNTY, NEW MEXICO

11-20-73