

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instructions
verse side)TE*
reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0338-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Peery Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT
Little Lucky Lake Devonian11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

S-29, T-15S, R-30E

14. PERMIT NO.

Regular

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3953 DF

12. COUNTY OR PARISH

Chavez

13. STATE

N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Ran retrievable bridge plug. Set @ 10,200'. Ran cement retainer & set @ 6597'.
2. Squeezed casing leak w/50 sx. Class C cement w/2% CFR-2.
3. Drilled out cement retainer @ 6597'. Drilled cement 6630-6750'.
4. Circulated sand off retrievable bridge plug @ 10,200'. Pulled bit. Pulled bridge plug, ran pkr.
5. Pulled tubing and packer. Ran RBP & set @ 10,455'. Spotted 2 sx. sand on plug. Pulled tubing & packer to 6934'. Spotted 60 sx. Type H cement w/.6% Haled 9 from 6600-6934'. SI w/500# on casing.
6. Drilled out cement 6360-6900' & stringers to 6950'. Pressured casing to 500#.
7. Pulled and reran tubing w/packer set @ 6500'. Tested 5-1/2" casing w/1500# for 30 minutes - OK.
8. Circulate sand off of RBP. Recover RBP.
9. Swab. Pulled tbq.
10. Ran Reda pump & returned to production.
11. On 24 hr. test dated 7-10-74 pumped 46 BND & 2270 BSW. GOR 1740. Gravity 46.2.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Asst. Dist. Supt.

DATE

7-12-74

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED
JUL 16 1974
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

APPROVED

JUL 17 1974

R. L. BEEKMAN

ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

RECEIVED

JUL 18 1974

O. C. C.
ARTESIA, OFFICE