

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM-25363	
2. NAME OF OPERATOR McClellan Oil Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. Drawer 730, Roswell, NM 88201		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & 1980' FWL		8. FARM OR LEASE NAME McC Champeau, Fed.	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3902' G.L.		10. FIELD AND POOL OR WILDCAT Double "L" South Area	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 31-T15S-R30E	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)		12. COUNTY OR PARISH Chaves	
		13. STATE NM	

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) Re-entry ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

- 3/25/85: Pulled dry hole marker.
- 3/27/85: Rigged up reverse unit. Drilled out cement plugs with 4-3/4" bit. Squeezed perfs in 5-1/2" casing at 3600'-3721' with 250 sx Class C with 2% CaCl₂.
- 3/27 to 4/2/85: Drilled out squeeze job and drilled out cement plugs in open hole to a total depth of 10,055'.
- 4/3/85: Ran Dresser CNL-LDT. Ran 10,032' of 4", 12.93 lb/ft, N-80 new casing. Cemented with 425 sx Class H with .5% Halad-22A, .3% CFR-2 and 5 lb/sk KCL. WOC - 10 hours. Temperature survey - TOC - 8500'. PBTD - 10,010'. Nippled up wellhead. Wait on completion unit.

18. I hereby certify that the foregoing is true and correct

SIGNED

Paul Kaye

TITLE

Operations Manager

DATE

4/15/85

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
PETER W. CHESTER
DATE

APR 18 1985

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side

RECEIVED

APR 22 1985

O.C.D.
HOBBS OFFICE