

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-00519
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. Z3756
7. Lease Name or Unit Agreement Name State LLA
8. Well No. 1
9. Pool name or Wildcat Little Lucky Lake Devonian
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3937 GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Matador Operating Company
3. Address of Operator 415 W. Wall, Ste 1101, Midland, TX 79701	4. Well Location Unit Letter C : 659 Feet From The North Line and 1979 Feet From The West Line Section 32 Township 15S Range 30E NMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3937 GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to 11,147' MVD (TVD 11,057'). Bottom hole location 181' N, 410' E of surface location 659 FNL, 1979 FWL Sec 32-15S-30E. Displacement 448'.

Ran 261 jts 5-1/2" 17#, N-80 and J-55 LT&C new csg. Tally 11,157.9 OA, set @ 11,146' KB w/ DV tool @ 10,626. Dowell Schmulberger cemented: Mix & pump 20 bbls CW100 chemical wash followed by 125 sx Class H, 50/50 poz, 2% gel, 2% expanding agent, .25% fluid loss additive, .25% dispersant, .1% retarder. Mix @ 14.8 ppg, 1.26 ft3/sk. Displace w/12 bbls fresh water 248 bbls mud. Good circulation, did not bump plug 1 bbl over displacement. Drop bomb, open DV tool w/ 700 psi and circ hole. Cement 2nd stage w/ 20 bbls CW100 chemical wash and 270 sx same cement. Displace w/ fresh water PD @ 4:14 PM, 8-9-94. Pressure to 2700 and close tool. Release pressure and holds OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. F. Burke TITLE Operations Manager DATE 8-10-94
TYPE OR PRINT NAME R. F. Burke TELEPHONE NO. 915-687-5955

(This space for State Use)
ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

AUG 30 1994