

	X		

**(SUBMIT IN TRIPLICATE)**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Artesia  
Lease No. NM-01171  
Unit \_\_\_\_\_

RECEIVED

**JUL 17 1961**

**O. C. C.**  
**POSTAL OFFICE**

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	-X-		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Lease No. 205289                      TEXACO Inc.                      P.O.Box 728  
K. McIntosh Federal                      Hobbs, New Mexico                      July 14, 1961

Well No. 2 is located 330 ft. from N line and 1980 ft. from E line of sec. 34  
SE/4, SW/4, Sec. 34 T-15-S R-30-E NMPM  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Undesignated Chaves New Mexico  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4008 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to plug and abandon subject well as follows:

1. Spot 22 sack cement plug from total depth of 3,215' to 2,915'
2. Cut off 4 $\frac{1}{2}$ " OD casing at approximately 500' and recover 500' of casing. (Top of cement calculated at 515', inside 7 5/8" OD surface casing set at 640'.)
3. Spot 15 sack cement plug from 50' below to 50' above top of non-recoverable 4 $\frac{1}{2}$ " OD casing.
4. Spot 15 sack cement plug at the surface inside 7 5/8" OD casing, install 4" marker 4' above ground level as per U.S.G.S. regulations

**I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.**

and clean location. For inspection by U.S.G.S.

Company ----- TEXACO Inc.

Address P.O. Box 728

Hobbs, New Mexico

J. G. Blevins, Jr.

By L. C. Merriam

Title Assistant District Superintendent