

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions
verse side)

NM 03906-A

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. NAME OF OPERATOR **B. W. P., Inc.**

3. ADDRESS OF OPERATOR **1012 Alpine, Midland, Texas 79701**

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
1388 FNL & 660 FWL, Sec. 7, T-7-S, R-31-E
1980

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
4314 DF

5. LEASE IDENTIFICATION AND SERIAL NO.
6-3906-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
General American Federal

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Lone Mississippian

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
7-7-31

12. COUNTY OR PARISH
Chaves

13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Completion of Well Abandonment : work completed 3-14-71.
Cement Plug 8110' back to 7870' in 5 1/2" Casing.
Pulled 3990' of 5 1/2" Casing.
Cement Plug 4040' back to 3940'.
Cement Plug 8 5/8 Casing Seat: 3187' back to 2975'.
Pulled 1130' of 8 5/8 Casing.
Cement Plug 1180' back to 1080'.
Cement Plug in 13 3/8 Surface Pipe.

Cementing Affidavit attached; prepared by Midland Casing Pullers.

Tank Battery has not been dismantled. This will be done and burning pit covered in sixty days. Final report will be submitted.

RECEIVED

APR 22 1971

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED *H. H. Halloran* TITLE Manager

DATE 4-22-71

(This space for Federal or State office use)

APPROVED BY *H. L. BEEKIN*
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

APPROVED
MAR - 9 1976
H. L. BEEKIN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-689229

847-485