

UNITED STATES OF AMERICA  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

15678

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Railroad Mountain

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND  
SUBVY OR AREA

Sec. 8, T-8S, R-31E

12. COUNTY OR PARISH

Chaves

13. STATE

N. Mex.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Harvey E. Yates Company, Inc.

3. ADDRESS OF OPERATOR

Ste. 1000 Security Nat'l Bank Bldg. Roswell, N.M. 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface

660' FNL &amp; FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4225' DF

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) run casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11/3/76 TD 10150'. Working stuck drill pipe, worked 45' out of hole.

11/4/76 TD 10150'. Trip in hole, backed off fish &amp; left 3 drill collars in hole.

11/5/76 TD 9956'. Circulating.

11/6/76 Ran 250 joints @ 9921'; 4½, 11.6# J-55 &amp; N-80 rng 3 8 rd casing. Set &amp; cemented @ 9933' with 600 sx of Cl "H", ¾ of 1% CFR-2, 5# KCL. PD @ 3:15 a.m., 11/6/76. Waiting on cement 24 hours.

RECEIVED

NOV 26 1976

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE Vice President

DATE 11/18/76

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE NOV 29 1976

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

RECEIVED

NOV 29 1976

O. C. C.  
ARTESIA, OFFICE

RECEIVED

SEP 8 1976

OIL CONSERVATION COMM.  
HOBBS, N. M.